

# SEDUTA LUNGA


Seduta Lunga is an IP55-rated, vandal resistant, illuminated bench made of Corten steel that is perfect for outdoor gardens, parks and other sitting areas. It uses stripLEDs in 2700K or 3000K for illumination under the bench.



## TECHNICAL DATA

<b>Wattage</b>	9.6W per 3.28 feet (1 m)
<b>Power Supply</b>	Remote 24VDC, not included. See page 2.
<b>Light Source</b>	StripLED
<b>Construction</b>	Body: Corten Steel
<b>CCT</b>	2700K, 3000K
<b>CRI</b>	>90
<b>Delivered Lumens</b>	790 lm per 3.28 feet (3000K)
<b>Efficacy</b>	82.3 lm/W (3000K)
<b>Optics</b>	Narrow
<b>Finishes</b>	Corten
<b>Fixture Dimensions</b>	78.74" l x 17.72" w x 17.72" h
<b>IP Rating</b>	IP55

Fixture Dimensions



## ORDERING INFORMATION

Example: R70.082.6.27.US. Power supplies sold separately.

R70.082	6		US
<b>Model No.</b>	<b>Finish</b>	<b>CCT</b>	
R70.082	6 - Corten	27 - 2700K 30 - 3000K	US

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00680</a>	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 20W, Class 2, IP66	1-1
<a href="#">PPLT00685</a>	Non-Dim	120-277VAC to 24VDC, 25W, Class 2, IP67	1-2
<a href="#">PPLT00690</a>	ELV / TRIAC & 0-10V Dimming	120-277VAC to 24VDC, 40W, Class 2, IP67	1-3
<a href="#">PPLT00691</a>	Non-Dim	120-277VAC to 24VDC, 60W, Class 2, IP67	1-5
<a href="#">PPLT00543</a>	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-8

## Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
<a href="#">PPLT00530</a>	L3DAE / L3D0	L3DA/L3D0	100%-1%	Hi-Lume™ 0.1% EcoSystem™ or 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-8

For other power supply options consult factory.

## PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: