


Seduta Lunga is an IP55-rated, vandal resistant, illuminated bench made of Corten steel that is perfect for outdoor gardens, parks and other sitting areas. It uses stripLEDs in 2700K or 3000K for illumination under the bench.



TECHNICAL DATA

Wattage	9.6W per 3.28 feet (1 m)
Power Supply	Remote 24VDC, not included. See page 2.
Light Source	StripLED
Construction	Body: Corten Steel
CCT	2700K, 3000K
CRI	>90
Delivered Lumens	790 lm per 3.28 feet (3000K)
Efficacy	82.3 lm/W (3000K)
Optics	Narrow
Finishes	Corten
Fixture Dimensions	78.74" l x 17.72" w x 17.72" h
IP Rating	IP55

Fixture Dimensions



ORDERING INFORMATION

Example: R70.082.6.27.US. Power supplies sold separately.

R70.082	6		US
Model No.	Finish	CCT	
R70.082	6 - Corten	27 - 2700K 30 - 3000K	US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00284	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, DAMP	1-8
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-8

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3DAE / L3D0	L3DA/L3D0	100%-1%	Hi-Lume™ 0.1% EcoSystem™ or 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-8

DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures 9.6W
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-8

For other power supply options consult factory.

PHOTOMETRIC DATA

*Coming Soon**Job Name/Date:**Fixture Type Designation:*