

TECHNICAL CATALOG 2024

designplan[®] 


STRAL

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

BASE




Inox Natural





Inox Graphite



Inox Bronze



Frame in AISI 316L stainless steel and polycarbonate lamp body, including the part recessed in the ground. Stainless steel fixing screws with color matched to the finish. Horizontal or vertical asymmetrical reflector. Optics from 21°, 45° and 65° at 2700K, 3000K and 4000K. Installation in the ground and/or on the floor through polyethylene outer casing. 0.31 inches extra-clear tempered glass. Integrated power supply. HCT surface finish available in three variants.




Emission



21°

Color	2700K	3000K	4000K
1086 lm	1100 lm	1226 lm	


Power
10W



45°

Color	2700K	3000K	4000K
1086 lm	1100 lm	1226 lm	


Power
10W



65°


Color	2700K	3000K	4000K
1086 lm	1100 lm	1226 lm	

Power
10W





Accessories

IP66 IP67 IK08 lm



BASE CASING
PT54000




Emission



21°

Color	2700K	3000K	4000K
	1629 lm	1650 lm	1839 lm


Power
15W



45°

Color	2700K	3000K	4000K
	1629 lm	1650 lm	1839 lm


Power
15W



65°


Color	2700K	3000K	4000K
	1629 lm	1650 lm	1839 lm

Power
15W





Accessories

IP66 IP67 IK08 lm



BASE CASING
PT54000




Emission



21°

Color	2700K	3000K	4000K
	1086 lm	1100 lm	1226 lm


Power
10W



45°

Color	2700K	3000K	4000K
	1086 lm	1100 lm	1226 lm


Power
10W



65°


Color	2700K	3000K	4000K
	1086 lm	1100 lm	1226 lm

Power
10W





Accessories

- IP66
- IP67
- IK08
-
- lm



BASE CASING
PT54000




Emission



21°

Color	2700K	3000K	4000K
1629 lm	1650 lm	1839 lm	


Power
15W



45°

Color	2700K	3000K	4000K
1629 lm	1650 lm	1839 lm	


Power
15W



65°


Color	2700K	3000K	4000K
1629 lm	1650 lm	1839 lm	

Power
15W



Accessories

- IP66
- IP67
- IK08
-
- lm



BASE CASING
PT54000