


Goccia is a family of outdoor in-grade step lights that are ideal for accent and pathway guidance lighting. They are available in round or square versions, 3 sizes, static white or RGB, and that can be installed flush with the surface using an outer casing, or wall mounted. Goccia 1.4 is the Ø1.0" round, static white version. (Not suitable for use in immersion in swimming pools or fountains).



TECHNICAL DATA

Wattage / Input	1.5W (24VDC)
Power Supply	Remote, not included. See page 2.
Construction	Body: Polyurethane Resin Cable Length: 4.92' standard (16.4" available)
CCT	2200K, 2700K, 3000K, 4000K
CRI	>80
BUG Rating	B0-U2-G0 (3000K)
Delivered Lumens	15 lm (3000K)
Efficacy	10 lm/W (3000K)
Optics	Diffuse
Fixture Dimensions	Ø1.02" x 0.98" h
Fixture Weight	0.13 lbs
LED Source	1 Mid-power LED
Lumen Maintenance	L80, B10 >60,000 hrs (Ta 25°C)
Color Consistency	3-Step MacAdam
Operating Temp.	-20°C to +45°C
IP Rating	IP65, IP68
IK Rating	IK10
Walkover	Yes

Fixture Dimensions



ORDERING INFORMATION

Example: GA14000000N0DR or GA14000000N0DR-1. Accessories / Power Supplies ordered separately.

GA1400	0000		0D	R	
Model No.		CCT	Optics	Finish	Cable Length
GA1400	0000	N - 2200K F - 2700K 5 - 3000K 9 - 4000K	0D - Diffuse	R - Resin	4.92' standard 1 - 16.40'

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC - *For use as in-grade uplights*

Part Number	Description	Input/Output	# of Fixtures
PPLT00149	Non-Dim	120VAC to 24VDC, 10W, Class 2, IP65	1-5
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	7-53

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-51

SUGGESTED POWER SUPPLIES

24VDC - *For use in fountains and swimming pools*

Part Number	Description	Input/Output	# of Fixtures
FPV-100110024	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 96W, Class 2, NEMA 4	1-51
FPV-100000024	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, NEMA 4	1-53
FPV-100100024	0-10V Dimming (2 channels)	120-277VAC to 24VDC, 26W, Class 2, IP66	1-106

DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715


Part Number	Description	Input/Output	# of Fixtures
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-51

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:


ACCESSORIES - Installation



WCA09

Outer Casing

For in-grade use



WCA25

Outer Casing


For Plasterboard

PHOTOMETRIC DATA

Note: All photometry is 3000K

Maximum Candela = 5.1

— C0 - C180
— C90 - C270



PHOTOMETRIC FILENAME : NEW_GOCCIA_1.4_D_3000K_1.5W_24VDC.IES

Job Name/Date:

Fixture Type Designation: