
# GOCCIA 1.9


Goccia is a family of outdoor step lights that are ideal for accent and pathway guidance lighting. They are available in round or square versions, 3 sizes, static white or RGB, and that can be installed flush with the surface using an outer casing, or wall mounted. Goccia 1.9 is the 1.0" square, RGB version. (Not suitable for use in immersion in swimming pools or fountains).

#### **TECHNICAL DATA**

Wattage / Input	1.2W (12VDC)
Power Supply	Remote, not included. See page 2.
Construction	Body: Polyurethane Resin
	Cable Length: 4.92' standard (16.4" available)
ССТ	RGB
BUG Rating	B0-U1-G0
Delivered Lumens	4 lm: (R) 1 lm, (G) 2 lm, (B) 1 lm
Efficacy	3.3 lm/W
	(R) 0.83 lm/W, (G) 1.67 lm/W, (B) 0.83 lm/W
Optics	Diffuse
Fixture Dimensions	1.02" x 1.02" x 0.98" h
Fixture Weight	0.20 lbs
LED Source	1 Mid-power, Full-color LED
Lumen Maintenance	L80, B10 >50,000 hrs (Ta 25°C)
Color Consistency	—
Operating Temp.	-20°C to +45°C
IP Rating	IP65, IP68
IK Rating	IK10
Walkover	Yes



**Fixture Dimensions** 



#### **ORDERING INFORMATION**

Example: GA19500P0060DR or GA19500P0060DR-1. Accessories / Power Supplies ordered separately.

GA1950	0P00	6	0D	R	
Model No. GA1950	0P00	CCT 6 - RGB	Optics 0D - Diffuse	Finish R - Resin	<b>Cable Length</b> 4.92' standard <b>1</b> - 16.40'

Job Name/Date:

Fixture Type Designation:

## designplan®

datasheet



datasheet

#### SUGGESTED POWER SUPPLIES

12VDC - For use as in-grade uplights

Part Number	Description	Input/Output	# of Fixtures
PPLT00288-P12	DMX / RDM (Field Addressable) / DALI (4 Channels)	120-277VAC to 12VDC, 100W, Class 2	1-64

#### SUGGESTED POWER SUPPLIES

12VDC - For use in fountains and swimming pools

Part Number	Description	Input/Output	# of Fixtures
FPV-060EL0012	DMX / RDM (Field Addressable) / DALI (4 Channels)	120-277VAC to 12VDC, 60W, Class 2, NEMA 4	1-40


For other power supply options consult factory.

#### **ACCESSORIES - Installation**



04.21"


WCA12 Outer Casing For in-grade use



WCA30 Outer Casing For Plasterboard

### PHOTOMETRIC DATA

Note: All photometry is 3000K



PHOTOMETRIC FILENAME : NEW\_GOCCIA\_1.9\_D\_RGB\_1.2W\_12VDC.IES

Job Name/Date:

Fixture Type Designation: