
designplan@

datasheet


Goccia is a family of outdoor step lights that are ideal for accent and pathway guidance lighting. They are available in round or square versions, 3 sizes, static white or RGB, and that can be installed flush with the surface using an outer casing, or wall mounted. Goccia 1.9 is the 1.0" square, RGB version. (Not suitable for use in immersion in swimming pools or fountains).

TECHNICAL DATA

1.2W (12VDC)		
Remote, not included. See page 2.		
Body: Polyurethane Resin		
Cable Length: 4.92' standard (16.4" available)		
RGB		
B0-U1-G0		
4 lm: (R) 1 lm, (G) 2 lm, (B) 1 lm		
3.3 lm/W		
(R) 0.83 lm/W, (G) 1.67 lm/W, (B) 0.83 lm/W		
Diffuse		
1.02" x 1.02" x 0.98" h		
0.20 lbs		
1 Mid-power, Full-color LED		
L80, B10 >50,000 hrs (Ta 25°C)		
_		
-20°C to +45°C		
IP65, IP68		
IK10		
Yes		



Fixture Dimensions



ORDERING INFORMATION

Example: GA19500P0060DR or GA19500P0060DR-1. Accessories / Power Supplies ordered separately.

GA1950	0P00	6	0D	R	
Model No.		ССТ	Optics	Finish	Cable Length
GA1950	0P00	6 - RGB	0D - Diffuse	R - Resin	4.92' standard 1 - 16.40'

Job Name/Date: Fixture Type Designation:

F:

F: 908-996-7042

P: 908-996-7710

1 of 2

datasheet

SUGGESTED POWER SUPPLIES


12VDC

Part Number	Description Input/Output		# of Fixtures
PPLT00162	Non-Dim	120-277VAC to 12VDC, 20W, Class 2, IP64	1-13
PPLT00652	0-10V Dimming 120-277VAC to 12VDC, 30W, Class 2		1-20
PPLT00654	0-10V Dimming	120-277VAC to 12VDC, 50W, Class 2	1-33
PPLT00134	Non-Dim	120-277VAC to 12VDC, 60W, Class 2, IP64	1-40


For other power supply options consult factory.

ACCESSORIES - Installation






WCA12 Outer Casing For in-grade use



WCA30Outer Casing
For Plasterboard

PHOTOMETRIC DATA

Note: All photometry is 3000K



PHOTOMETRIC FILENAME : NEW_GOCCIA_1.9_D_RGB_1.2W_12VDC.IES

Job Name/Date:

Fixture Type Designation: