


Goccia is a family of outdoor step lights that are ideal for accent and pathway guidance lighting. They are available in round or square versions, 3 sizes, static white or RGB, and that can be installed flush with the surface using an outer casing, or wall mounted. Goccia 2.8 is the Ø1.8" round, RGB version. (Not suitable for use in immersion in swimming pools or fountains).

TECHNICAL DATA

Wattage / Input	2W (24VDC)
Power Supply	Remote, not included. See page 2
Construction	Body: Polyurethane Resin Cable Length: 4.92' standard (16.4" available)
CCT	RGB
BUG Rating	B0-U2-G0
Delivered Lumens	18 lm: (R) 5 lm, (G) 12 lm, (B) 2 lm
Efficacy	9 lm/W: (R) 2.5 lm/W, (G) 6 lm/W, (B) 1 lm/W
Optics	Diffuse
Fixture Dimensions	Ø1.77" x 1.30" h
Fixture Weight	0.31 lbs
LED Source	6 Mid-power, Full-color LEDs
Lumen Maintenance	L80, B10 >50,000 hrs (Ta 25°C)
Color Consistency	—
Operating Temp.	-20°C to +45°C
IP Rating	IP65, IP68 IP69 (Water Temp Not Exceed 35° C)
IK Rating	IK10
Walkover	Yes



Fixture Dimensions



ORDERING INFORMATION

Example: GA28000P0060DR or GA28000P0060DR-1. Accessories / Power Supplies ordered separately.

GA2800	0P00	60	0D	R	
Model No.		CCT	Optics	Finish	Cable Length
GA2800	0P00	6 - RGB	0D - Diffuse	R - Resin	4.92' standard 1 - 16.40'

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES
24VDC - *For use as in-grade uplights*


Part Number	Description	Input/Output	# of Fixtures
PPLT00288-P12	DMX / RDM (Field Addressable) / DALI (4 Channels)	120-277VAC to 24VDC, 100W, Class 2	1-64

For other power supply options consult factory.

ACCESSORIES - Installation



WCA08
Outer Casing
For in-grade use




WCA26
Outer Casing
For Plasterboard



WL0100
Suction Cup

PHOTOMETRIC DATA

Note: All photometry is 3000K



Job Name/Date:

Fixture Type Designation: