GOCCIA 3.9


Goccia is a family of outdoor step lights that are ideal for accent and pathway guidance lighting. They are available in round or square versions, 3 sizes, static white or RGB, and that can be installed flush with the surface using an outer casing, or wall mounted. Goccia 3.9 is the 2.8" x 2.8" square, RGB version. (Not suitable for use in immersion in swimming pools or fountains).

TECHNICAL DATA


Wattage / Input	3.5W (24VDC)			
Power Supply	Remote, not included. See page 2.			
Construction	Body: Polyurethane Resin Cable Length: 4.92' standard (16.4" available)			
ССТ	RGB			
BUG Rating	B0-U3-G0			
Delivered Lumens	50 lm: (R) 15 lm, (G) 34 lm, (B) 7 lm			
Efficacy	14.3 lm/W: (R) 4.29 lm/W, (G) 9.71 lm/W, (B) 2 lm/W			
Optics	Diffuse			
Fixture Dimensions	2.76" x 2.76" x 1.42" h			
Fixture Weight	0.57 lbs			
LED Source	12 Mid-power, Full-color LEDs			
Lumen Maintenance	L80, B10 >50,000 hrs (Ta 25°C)			
Color Consistency	—			
Operating Temp.	-20°C to +45°C			
IP Rating	IP65, IP68			
IK Rating	IK10			
Walkover	Yes			

designplan®

datasheet



Fixture Dimensions



ORDERING INFORMATION

Example: GA39000P0060DR or GA39000P0060DR-1. Accessories / Power Supplies ordered separately.

GA3900	0P00	6	0D	R	
Model No.		ССТ	Optics	Finish	Cable Length
GA3900	0P00	6 - RGB	0D - Diffused	R - Resin	4.92' standard 1 - 16.40'

Job Name/Date:

Fixture Type Designation:

designplan®

datasheet

SUGGESTED POWER SUPPLIES

24VDC - For use as in-grade uplights

Part Number	Description	Input/Output	# of Fixtures
PPLT00288-P12	DMX / RDM (Field Addressable) / DALI (4 Channels)	120-277VAC to 24VDC, 100W, Class 2	1-20

SUGGESTED POWER SUPPLIES


24VDC - For use in fountains and swimming pools

Part Number	Description	Input/Output	# of Fixtures
FPV-060EL0012	DMX / RDM (Field Addressable) / DALI (4 Channels)	120-277VAC to 24VDC, 60W, Class 2, NEMA 4	1-20

For other power supply options consult factory.

ACCESSORIES - Installation






WCA10 Outer Casing For in-grade use


PHOTOMETRIC DATA

Note: All photometry is 3000K



PHOTOMETRIC FILENAME : NEW_GOCCIA_3.9_D_RGB_3.5W_24VDC.IES

Job Name/Date:



WCA28 Outer Casing For Plasterboard



WL0100 Suction Cup

Fixture Type Designation: