

MINI DOLPHIN


MINI DOLPHIN is a square underwater spotlight with linear illumination that is suitable for installation in pools with vinyl coating or tile. It has a stainless steel flange, and comes in static white, tunable white or RGBW with 6 cover colors, and a 5 year warranty.



TECHNICAL DATA

Wattage	14W (Static, Tunable), 11W (RGBW)
Power Supply	Remote Fountain/Pool Approved 24VDC Power Supply, not included. See page 2.
Construction	Body: Techopolymer Cable Length: 15 ft included
CCT	3000K, 4000K, 5000K Tunable White (2700K-4600K), RGBW
CRI	80
Delivered Lumens	2000 lm (120°, 3000K) 455.4 lm (RGBW)
Efficacy	100 lm/W (3000K) 41.4 lm/W (RGBW)
Optics	120°, 60°x10°
Finishes	Stainless Steel, Corian
Fixture Dimensions	5.71" x 5.63" x 6.57" h
Cutout Dimensions	5.08" x 4.92"
Fixture Weight	5.07 lbs
LED Source	4 SMD 3535 SHINEON (static white)
Working Temp	-20° / +50°
IP Rating	IP68
Warranty	5 Years

Fixture Dimensions



ORDERING INFORMATION

Example: MDP.W.24.68.AS.US. Power Supplies / Accessories ordered separately.

MDP		24	68		US
Model No.	CCT	Power	IP Rating	Optic	
MDP	W - 3000K N - 4000K C - 5500K TW - Tunable White (2800-4600K) RGBW - RGBW	24 - 24VDC	68 - IP68	FL - 120° AS - 60x10°	US

Job Name/Date:

Fixture Type Designation:


SUGGESTED POWER SUPPLIES

24VDC - Static, Tunable White or RGBW

Part Number	Description	Input/Output	# of Fixtures		
			Static	Tunable	RGBW
FPV-100110024	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 96W, Class 2, NEMA 4	1-5	1-5	1-6
FPV-100000024	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, NEMA 4	1-5	1-5	1-7
FPV-100100024	1-10V Dimming	120-277VAC to 24VDC, 100W, Class 2, NEMA 4	1-5	1-5	1-7
FPV-100EL0024	DMX / RDM (Field Addressable) / DALI	120-277VAC to 24VDC, 100W, Class 2, NEMA 4	1-4	1-4	1-4

For other power supply options consult factory.

ACCESSORIES - Installation




MDP-NC
Technopolymer
outercase
REQUIRED



CA-68-2-1
Monochromatic - Reel of Cable
15 feet of cable included - custom length on request


CA-68-4-1
Tunable White - Reel of Cable
15 feet of cable included - custom length on request



MDP-FL-Q
Stainless Steel Cover
REQUIRED

CA-68-5-1
RGBW - Reel of Cable
15 feet of cable included - custom length on request

COVER COLORS




MDP-FL-WC/SC/GC/AC/CC/BC
Corian Cover

Job Name/Date:

Fixture Type Designation:


PHOTOMETRIC DATA

Maximum Candela = 2693.1




PHOTOMETRIC FILENAME : MINI DOLPHIN 30K 60X10° - MDP-W.24.68.AS.IES

Maximum Candela = 2575.7




PHOTOMETRIC FILENAME : MINI DOLPHIN 40K 60X10° - MDP-N.24.68.AS.IES

Maximum Candela = 2614.3




PHOTOMETRIC FILENAME : MINI DOLPHIN 50K 60X10° - MDP-C.24.68.AS.IES

Maximum Candela = 28.9




PHOTOMETRIC FILENAME : MINI DOLPHIN RGBW (BLUE) 60X10° - MDP-RGBW.24.68.AS.B.IES

Maximum Candela = 273.3




PHOTOMETRIC FILENAME : MINI DOLPHIN RGBW (GREEN) 60X10° - MDP-RGBW.24.68.AS.G.IES

Maximum Candela = 24593.2



PHOTOMETRIC FILENAME : MINI DOLPHIN RGBW (RED) 60X10° - MDP-RGBW.24.68.AS.R.IES

Maximum Candela = 271.7



PHOTOMETRIC FILENAME : MINI DOLPHIN RGBW (WHITE) 60X10° - MDP-RGBW.24.68.AS.W.IES

Job Name/Date:

Fixture Type Designation: