

CIELO MAXI DMX RGBW



Cielo Maxi HP is a 10.0" round, IP67-rated, recessed downlight available in 4 versions and suitable for outdoor installation. Cielo Maxi HP DMX RGBW is a 28W RGBW version with 6 CREE "XML" RGBW LED. Available in 3 optic options and a stainless steel finish.



TECHNICAL DATA

Wattage	28W
Power Supply	Remote 24VDC, not included. See page 2.
Construction	Body: Die-cast Copper-free Aluminum Trim: Stainless Steel AISI 316L Lens: Tempered, Safety Glass Cable Length: 3.28'
CCT	RGBW
Delivered Lumens	981 lm (35°) 992 lm (25°) 1000 lm (12°)
Efficacy	35.0 lm/W (35°) 35.4 lm/W (25°) 35.7 lm/W (12°)
Optics	12°, 25°, 35°
Finishes	Stainless Steel
Fixture Dimensions	Ø10.00" x 10.47" h
Cutout Dimensions	Ø9.61"
Fixture Weight	12.6 lbs
LED Source	6 CREE "XML" RGBW LED
IP Rating	IP67
IK Rating	IK10

Fixture Dimensions



HOLE FOR RECESS

ORDERING INFORMATION

Example: 701313P.RGBW.12.SS. Power Supplies / Accessories ordered separately.

701313P	RGBW		SS
Model No.	CCT	Optic	Finish
701313P	RGBW	12 - 12° 25 - 25° 35 - 35°	SS - Stainless Steel

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00586	Non-Dim	120-277VAC to 24VDC, 40W, Class 2	1-1
PPLT00690	ELV / TRIAC & 0-10V Dimming	120-277VAC to 24VDC, 40W, Class 2, IP67	1-1
PPLT00681	Non-Dim	120-277VAC to 24VDC, 90W, Class 2, IP67	1-2
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-2

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00273	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 40W, Class 2	1-1
PPLT00530	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-2

For other power supply options consult factory.

ACCESSORIES



AC119

Honeycomb Louver for Cielo Maxi

PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: