CIELO MEDIUM HP

datasheet

Cielo Medium is a round, IP67-rated, recessed downlight available in 4 versions and suitable for outdoor installation. Cielo Medium HP is a 20W version with 3 CREE XHP35 LED. Available in 3 color temperatures, 3 optic options and a stainless steel finish. Suitable for use in open structures.



Fixture Dimensions





HOLE FOR RECESS

TECHNICAL DATA

Wattage	20W
Power Supply	Integral 120VAC
Construction	Body: Die-cast Copper-free Aluminum Trim: Stainless steel AISI 316L Lens: Tempered, Safety Glass Cable Length: 3.28’
CCT	2700K, 3000K, 4000K
Delivered Lumens	1733 lm (28°, 3000K) 1787 lm (10°, 3000K) 1863 lm (4°, 3000K)
Efficacy	86.7 lm/W (28°, 3000K) 89.4 lm/W (10°, 3000K) 93.2 lm/W (4°, 3000K)
Optics	4°, 10°, 28°
Finishes	Stainless Steel
Fixture Dimensions	Ø8.62” x 10.47” h
Cutout Dimensions	Ø8.27”
Fixture Weight	10.36 lbs
LED Source	3 CREE XHP35 LED
IP Rating	IP67
IK Rating	IK10

ORDERING INFORMATION

Example: 701308P.27.4.SS. Power Supplies ordered separately.

701308P			.	**SS**
Model No.	**CCT**	**Optic**		**Finish**
701308P	**27** - 2700K **30** - 3000K **40** - 4000K	**4** - 4° **10** - 10° **28** - 28°		**SS** - Stainless Steel

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825

© Copyright 2024 Designplan Lighting, Inc.

Published: November 18, 2026

P: 908-996-7710
F: 908-996-7042

CIELO MEDIUM HP

datasheet

ACCESSORIES



AC118
Honeycomb Louver for Cielo Medium

PHOTOMETRIC DATA

Note: All photometry is 3000K



PHOTOMETRIC FILENAME : CIELO MEDIUM HP_701308_4°.IES



PHOTOMETRIC FILENAME : CIELO MEDIUM HP_701308_10°.IES



PHOTOMETRIC FILENAME : CIELO MEDIUM HP_701308_28°.IES

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825

© Copyright 2024 Designplan Lighting, Inc.

Published: November 18, 2026

P: 908-996-7710
F: 908-996-7042