

CIELO MEDIUM DMX RGBW



Cielo Medium is a round, IP67-rated, recessed downlight available in 4 versions and suitable for outdoor installation. Cielo Medium HP DMX RGBW is a 14W version with a CREE "XML" RGBW LED. Available in RGBW with 3 optic options and a stainless steel finish.



TECHNICAL DATA

| | |
|---------------------------|---|
| Wattage | 14W |
| Power Supply | Remote 24VDC, not included. See page 2. |
| Construction | Body: Die-cast Copper-free Aluminum Trim: Stainless Steel AISI 316L Lens: Tempered, Safety Glass Cable Length: 3.28' |
| CCT | RGBW |
| Delivered Lumens | 435 lm (35°) 456 lm (25°) 480 lm (12°) |
| Efficacy | 31.1 lm/W (35°) 32.6 lm/W (25°) 34.3 lm/W (12°) |
| Optics | 12°, 25°, 35° |
| Finishes | Stainless Steel |
| Fixture Dimensions | Ø8.62" x 10.47" h |
| Cutout Dimensions | Ø8.27" |
| Fixture Weight | 10.36 lbs |
| LED Source | 1 CREE "XML" RGBW LED |
| IP Rating | IP67 |
| IK Rating | IK10 |

Fixture Dimensions



HOLE FOR RECESS

ORDERING INFORMATION

Example: 701309P.RGBW.12.SS. Power Supplies / Accessories ordered separately.

| 701309P | RGBW | | SS |
|-----------|------|----------------------------------|----------------------|
| Model No. | CCT | Optic | Finish |
| 701309P | RGBW | 12 - 12° 25 - 25° 35 - 35° | SS - Stainless Steel |

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC

| Part Number | Description | Input/Output | # of Fixtures |
|---------------------------|---|---|---------------|
| PPLT00685 | Non-Dim | 120-277VAC to 24VDC, 25W, Class 2, IP67 | 1-1 |
| PPLT00586 | Non-Dim | 120-277VAC to 24VDC, 40W, Class 2 | 1-2 |
| PPLT00681 | Non-Dim | 120-277VAC to 24VDC, 90W, Class 2, IP67 | 1-5 |
| PPLT00543 | 0-10V Dimming to 15% (-40°C / -40°F cold weather start) | 120-277VAC to 24VDC, 100W, Class 2 | 1-5 |

Suggested Lutron Compatible

| Part Number | Option | Lutron SKU | Dim Range | Description | Input/Output | # of Fixtures |
|---------------------------|----------------|------------|-----------|--|-----------------------------------|---------------|
| PPLT00273 | L3DAE / L3DA3W | L3DA | 100%-1% | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 24VDC, 40W, Class 2 | 1-2 |
| PPLT00530 | L3DAE / L3DA3W | L3DA | 100%-1% | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 24VDC, 96W, Class 2 | 1-5 |

For other power supply options consult factory.

ACCESSORIES




AC118

Honeycomb Louver for Cielo Medium

ACCESSORIES

Controllers (RGBW)



[PPWD00570](#) - RGBW DMX512+Wifi Controller

Touch Sensitive

Can be controlled by WiFi

Controls 3 zones synchronously and separately

PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: