

EASY LINE - Frost LL10


EASY LINE is a vertical, bendable LED strip that is IP65-IP68 rated ideal for fountains or swimming pools for panel installation in reinforced concrete with tiles or pool liner. It is available in Transparent, Frost, Clear or Total Light with static white, tunable white or RGB, and guarantees protection against UV rays and the corrosive action of salt and sodium hypochlorite. EASY LINE Frost has opal resin with a white outercasing. **Not cuttable in the field.**



TECHNICAL DATA

Wattage	11W / 3.28 ft (1 m)	
Power Supply	Remote Fountain/Pool Approved 24VDC Power Supply, not included. See page 2.	
Construction	Body: Opal Polyurethane Resin Outercase: White PVC	
CCT	2850K, 3150K, 4350K, 5500K (204 LED / 3.28') Warm White on request: 2000K, 2400K, 2700K	
CRI	85	
Delivered Lumens	620 lm / 3.28' (2850K) 570 lm / 3.28' (3150K)	590 lm / 3.28' (4350K) 620 lm / 3.28' (5500K)
Efficacy	56.4 lm/W (2850K) 51.8 lm/W (3150K)	51.6 lm/W (4350K) 56.4 lm/W (5500K)
Optics	120°	
Fixture Dimensions	0.37" w x 0.26" h x Various Lengths	
Bend Radius	2.36"	
LED Source	SMD 3014	
LED Spacing	204 LED per 3.28 ft (1 m), 0.20" between LEDs	
Lumen Maintenance	L80, B10>50,000 hrs	
Color Consistency	2-3-Step MacAdam	
Operating Temp.	-22°F to 131°F	
IP Rating	IP65 / IP68	

Fixture Dimensions



NOT CUTTABLE IN THE FIELD

**MUST USE SUITABLE APPROVED
FOUNTAIN & SWIMMING POOL
POWER SUPPLY WHICH
IS REMOTELY MOUNTED**

ORDERING INFORMATION

Example: LL10E-N.24.68.FX.US. Power Supplies / Accessories ordered separately.

LL10E	-		.	24	.		.	F	.		.	US
Model No.	CCT		Power		IP Rating				Cable Exit			
LL10E - 204 LED / 3.28' (1 m)	V - 2850K	Warm White	24 - 24VDC	65 - IP65	F - Frost	X - End Feed	US					
<div>NOTE: Available in lengths up to 75 feet. Please specify length when ordering.</div>	W - 3150K	On Request		68 - IP68		Z - Back Feed						
	N - 4350K	V8 - 2000K				NOTE: Back Feed						
	C - 5500K	V2 - 2400K				(Z) only available on IP65 versions						
		V5 - 2700K										

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES**24VDC - TO BE USED WITH FOUNTAIN / SWIMMING POOLS**

Part Number	Description	Input/Output	# of Fixtures
FPV-100110024	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 100W, Class 2, NEMA 4	1-6
FPV-100000024	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, NEMA 4	1-7
FPV-100100024	0-10V Dimming (2 Channels)	120-277VAC to 24VDC, 100W, Class 2, NEMA 4	1-14


SUGGESTED POWER SUPPLIES**24VDC - TO BE USE FOR INDOOR/OUTDOOR USE - NOT Fountain / Swimming Pool**

Part Number	Description	Input/Output	# of Fixtures
PPLT00690	ELV / TRIAC & 0-10V Dimming	120-277VAC to 24VDC, 40W, Class 2, IP67	1-2
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-7



Suggested Lutron Compatible - **FOR INDOOR/OUTDOOR USE ONLY**

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00273	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 40W, Class 2	1-2
PPLT00530	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-6



For other power supply options consult factory.

ACCESSORIES - Installation



CLIP-AC-9.5x6.5-AC
Harmonic steel clips




OUT-S-9.5x6.5.F/W
Flexible Silicone Outercase
L=16.4"



PRO-AL-9.5x6.5-AL
Rigid Aluminum Outercase
L=9.84'



CLIP-S-9.5x6.5.F/W
Silicone Clip




CABLE-BOX
Cable box

Job Name/Date:

Fixture Type Designation:


POWER CABLE EXIT / AREA WITH REDUCED LIGHT



PHOTOMETRIC DATA


2850K

Maximum Candela = 162.4




3150K

Maximum Candela = 151.1




4350K

Maximum Candela = 154.4



5500K

Maximum Candela = 164



Job Name/Date:

Fixture Type Designation: