

# TREVI S 2.7


Trevi S is a suspended version of the distinctive Trevi linear profile that is a simple and elegant lighting solution with a wide range of optics suitable for outdoor applications, such as the terraces of hotels and restaurants or indoor applications, such as reception areas. Trevi S 2.7 is the 47.8" length version offering RGBW light with diffuse or elliptical optics.



## TECHNICAL DATA

<b>Wattage / Input</b>	50W (24VDC)
<b>Power Supply</b>	Remote, not included. See page 2.
<b>Construction</b>	End Caps: AISI 316L Stainless Steel Heat Sink: Internal Anticorodal Aluminum Lens: Transparent Polycarbonate Cable Length: 16.4 ft
<b>CCT</b>	RGBW
<b>BUG Rating</b>	B1-U1-G0 (3000K, 39°x95°, Diffuse & RGBW, Diffuse) B2-U1-G0 (RGBW, 39°x95°)
<b>Delivered Lumens</b>	2870 lm (Diffuse) (R) 324 lm (G) 1197 lm (B) 224 lm (W) 1341 lm (3000K)
<b>Efficacy</b>	57.4 lm/W (Diffuse) (R) 6.5 lm/W (G) 24.0 lm/W (B) 4.5 lm/W (W) 26.8 lm/W
<b>Optics</b>	39°x95°, Diffuse
<b>Finish</b>	Polycarbonate
<b>Fixture Dimensions</b>	Ø1.97" x 47.76" l
<b>Fixture Weight</b>	8.82 lbs
<b>LED Source</b>	336 mid-power LEDs
<b>Lumen Maintenance</b>	60,000h L80 B10 (Ta 25°C)
<b>Color Consistency</b>	—
<b>Operating Temp.</b>	-4°F - 113°F
<b>IP Rating</b>	IP65, IP68
<b>Impact Rating</b>	IK10

Fixture Dimensions



## ORDERING INFORMATION

Example: TR2700000070WP+WMA07+WMA04 Accessories / Power Supplies ordered separately.

TR27000000	70		P	+	WMA07	+	
<b>Model No.</b>	<b>CCT</b>	<b>Optics</b>	<b>Finish</b>		<b>Suspension Kit</b>		<b>Clip</b>
TR27000000	70 - RGBW	W - 39°x95° D - Diffuse	P - Polycarbonate		WMA07 - Suspension Kit		WMA04 - Clip Pair WMA05 - Pair of tamper-resistant Clips

Job Name/Date:

Fixture Type Designation:


## SUGGESTED POWER SUPPLIES

24VDC - RGBW

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00288-P24</a>	DMX / RDM (Field Addressable) / DALI	120-277VAC to 24VDC, 100W, Class 2, Dry	1 - 1


For other power supply options consult factory.

## ACCESSORIES - Installation (REQUIRED)




### WMA04

Clips Pair



### WMA05

Pair of temper-resistant clips



### WMA07

Suspension Kit

## ACCESSORIES

Controllers (RGBW)



### PPWD00570 - RGBW DMX512+Wifi Controller

Touch Sensitive

Can be controlled by WiFi

Controls 3 zones synchronously and separately


Job Name/Date:

Fixture Type Designation:

## PHOTOMETRIC DATA


Note all Photometry is 3000K

Maximum Candela = 883.3




PHOTOMETRIC FILENAME : TREVI\_2.7\_W\_39X95\_3000K\_50W\_24VDC.IES

Maximum Candela = 534.1




PHOTOMETRIC FILENAME : TREVI\_2.7\_D\_3000K\_50W\_24VDC.IES

Maximum Candela = 1945



PHOTOMETRIC FILENAME : TREVI\_2.7\_W\_39X95\_RGBW\_50W\_24VDC.IES

Maximum Candela = 1079.5



PHOTOMETRIC FILENAME : TREVI\_2.7\_D\_RGBW\_50W\_24VDC.IES

Job Name/Date:

Fixture Type Designation: