

TREVI S

SUSPENDED FOR OUTDOOR APPLICATIONS



Combined with a suspended configuration, the distinctive characteristics of the Trevi profile, a tubular polycarbonate screen with end caps in AISI 316L stainless steel, result in Trevi S: a lighting solution with a simple elegance. Ideal for both indoor and outdoor applications, this family of suspended profiles is suitable for private residences and hospitality reception areas, thanks to the availability of rotationally symmetrical, elliptical and diffuse optics.



Trevi S 2.2, 3000K, 62W, diffuse.

TREVI S

2200K 2700K 3000K 4000K RGB RGBW

24VDC
7W up to 75W
CRI 80
White tones: up to 6726 lm (3000K, 38°x94°)
RGB: up to 1197 lm, R: 266 lm G: 765 lm B: 166 lm (diffuse version)
RGBW: up to 4305 lm, R: 486 lm G: 1796 lm B: 336 lm W: 2011 lm (3000K, diffuse)
Optics
Fixed: 10°, 29°, 42°, diffuse
Elliptical: 15°x47°, 36°x94°, 38°x94°, 39°x95°
IP65 IP68 IK10



TREVI 1.0 (optics; diffuse; RGB) Ø0.98"x24.13"	TREVI 2.0 TREVI 2.6 (RGBW) Ø1.97"x25.71"	TREVI 2.3 Ø1.97"x25.71"
TREVI 1.1 (optics; diffuse; RGB) Ø0.98"x47.56"	TREVI 2.1 TREVI 2.7 (RGBW) Ø1.97"x47.76"	TREVI 2.4 Ø1.97"x47.76"
TREVI 1.2 (optics; diffuse; RGB) Ø0.98"x70.98"	TREVI 2.2 TREVI 2.8 (RGBW) Ø1.97"x69.80"	TREVI 2.5 Ø1.97"x69.80"

Accessories:
Clips pair
Pair of tamper-resistant clips

Required pair of clips, not included. Required suspension kit, not included