

EASY LINE - Transparent LLRGB1

EASY LINE is a vertical, bendable LED strip that is IP65-IP68 rated ideal for fountains or swimming pools for panel installation in reinforced concrete with tiles or pool liner. It is available in Transparent, Frost, Clear or Total Light with static white, tunable white or RGB, and guarantees protection against UV rays and the corrosive action of salt and sodium hypochlorite. EASY LINE Transparent has a transparent outercasing. **Not cuttable in the field.**




UL 676



TECHNICAL DATA

Wattage	15W / 3.28 ft (1 m)
Power Supply	Remote Fountain/Pool Approved 24VDC Power Supply, not included. See page 2.
Construction	Body: Transparent Resin Outercase: Transparent UV-treated PVC
CCT	RGB (60 LED / 3.28')
CRI	80
Delivered Lumens	350 lm / 3.28' (1 m)
Efficacy	23.3 lm/W
Optics	120°
Fixture Dimensions	0.55" w x 0.26" h x Various Lengths
Bend Radius	2.36"
LED Source	SMD 5050
LED Spacing	60 LED per 3.28 ft (1 m), 0.63" between LEDs
Lumen Maintenance	L80,B10>50,000 hrs
Color Consistency	2-3-Step MacAdam
Operating Temp.	-22°F to 131°F
IP Rating	IP65 / IP68

Fixture Dimensions



NOT CUTTABLE IN THE FIELD

**MUST USE SUITABLE APPROVED
FOUNTAIN & SWIMMING POOL
POWER SUPPLY WHICH
IS REMOTELY MOUNTED**

ORDERING INFORMATION

Example: LLRGB1E-24.68.T.X.US Power Supplies / Accessories ordered separately.

LLGB1E	-	24	.		.	T	.	X	.	US
Model No.	Power		IP Rating				Cable Exit			
LLRGB1E - 60 LED / 3.28' (1 m)	24 - 24VDC		65 - IP65 68 - IP68		T - Transparent		X - End Feed		US	
NOTE: Available in lengths up to 75 feet. Please specify length when ordering.										

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC - **TO BE USED WITH FOUNTAIN / SWIMMING POOLS**

Part Number	Description	Input/Output	# of Fixtures
FPV-100EL0024	DMX/RDM(Field Addressable)/Dali, 4 Channels	120-277VAC to 24VDC, 100W, Class 2, IP66, NEMA 4X	1-5


SUGGESTED POWER SUPPLIES

24VDC - **TO BE USE FOR INDOOR/OUTDOOR USE - NOT** Fountain / Swimming Pool


Part Number	Description	Input/Output	# of Fixtures
PPLT00288-P24	DMX/RDM(Field Addressable)/Dali, 4 Channels	120-277VAC to 24VDC, 100W, Class 2, DRY	1-5


For other power supply options consult factory.

ACCESSORIES - Installation





CLIP-AC-14x6.5-AC
Harmonic steel clips







OUT-S-14x6.5.F/W
White Flexible Silicone
Outercase L=16.40'






PRO-AL-14x6.5-AL
Rigid Aluminum Outercase
L=9.84'






CLIP-S-14x6.5.F/W
Silicone Clip




CABLE-BOX
Cable box

POWER CABLE EXIT / AREA WITH REDUCED LIGHT



Opposite side



X. End feed

Job Name/Date:

Fixture Type Designation: