

# EASY LINE - Transparent LLRGB3

EASY LINE is a vertical, bendable LED strip that is IP65-IP68 rated ideal for fountains or swimming pools for panel installation in reinforced concrete with tiles or pool liner. It is available in Transparent, Frost, Clear or Total Light with static white, tunable white or RGB, and guarantees protection against UV rays and the corrosive action of salt and sodium hypochlorite. EASY LINE Transparent has a transparent outercasing. **Not cuttable in the field.**





UL 676



## TECHNICAL DATA

<b>Wattage</b>	15.5W / 3.28 ft (1 m)
<b>Power Supply</b>	Remote Fountain/Pool Approved 24VDC Power Supply, not included. See page 2.
<b>Construction</b>	Body: Transparent Resin Outercase: Transparent UV-treated PVC
<b>CCT</b>	RGB (120 LED / 3.28')
<b>CRI</b>	80
<b>Delivered Lumens</b>	550 lm / 3.28' (1 m)
<b>Efficacy</b>	35.5 lm/W
<b>Optics</b>	120°
<b>Fixture Dimensions</b>	0.55" w x 0.26" h x Various Lengths
<b>LED Source</b>	SMD 3535
<b>LED Spacing</b>	120 LED per 3.28 ft (1 m), 0.33" between LEDs
<b>Lumen Maintenance</b>	L80,B10>50,000 hrs
<b>Color Consistency</b>	2-3-Step MacAdam
<b>Operating Temp.</b>	-22°F to 131°F
<b>IP Rating</b>	IP65 / IP68

Fixture Dimensions



**NOT CUTTABLE IN THE FIELD**

## ORDERING INFORMATION

Example: LLRGB3-24.68.T.US Power Supplies / Accessories ordered separately.

LLGB3	-	24	.		.	T	.	US
<b>Model No.</b>		<b>Power</b>		<b>IP Rating</b>				
LLRGB3 - 120 LED / 3.28' (1 m)		24 - 24VDC		65 - IP65 68 - IP68		T - Transparent		US

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

24VDC - **TO BE USED WITH FOUNTAIN / SWIMMING POOLS**

Part Number	Description	Input/Output	# of Fixtures
<a href="#">FPV-100EL0024</a>	DMX/RDM(Field Addressable)/Dali, 4 Channels	120-277VAC to 24VDC, 100W, Class 2, NEMA 4	1-5


## SUGGESTED POWER SUPPLIES

24VDC - **TO BE USE FOR INDOOR/OUTDOOR USE - NOT** Fountain / Swimming Pool



Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00288-P24</a>	DMX/RDM(Field Addressable)/Dali, 4 Channels	120-277VAC to 24VDC, 100W, Class 2, DRY	1-5

For other power supply options consult factory.



## ACCESSORIES - Installation





**CLIP-AC-14x6.5-AC**  
Harmonic steel clips




**OUT-S-14x6.5.F/W**  
White Flexible Silicone  
Outercase L=16.40'



**PRO-AL-14x6.5-AL**  
Rigid Aluminum Outercase  
L=9.84'




**CLIP-S-14x6.5.F/W**  
Silicone Clip




**CABLE-BOX**  
Cable box

## POWER CABLE EXIT / AREA WITH REDUCED LIGHT



Opposite side



X. End feed

Job Name/Date:

Fixture Type Designation: