

FLEA MINI DOWNLIGHT RGBW

FLEA is a family of IP67-rated round or square recessed wall / in-grade or downlights available in static white, RGBW, and and underwater version (IP68). FLEA MINI Downlight RGBW is offered round (Ø1.4") or square (1.4" sq.) with RGBW light, 2 optics options, and 3 standard finishes.



FLEA MINI Downlight Round RGBW



FLEA MINI Downlight Square RGBW

Fixture Dimensions - See page 2

TECHNICAL DATA

Wattage	5W
Power Supply	Remote 24VDC, not included. See page 2.
Construction	Housing: Anticorodal Aluminum Lens: Extra Clear Tempered Glass
CCT	RGBW
BUG Rating	—
CRI	—
Delivered Lumens	174 lm: (R) 25 lm, (G) 52 lm, (B) 13 lm, (W) 84 lm (6500K)
Efficacy	34.8 lm/W: (R) 5 lm/W lm, (G) 10.4 lm/W, (B) 2.6 lm/W, (W) 16.8 lm (6500K)
Optics	30°, Diffuse
Finishes	Anodized Matte Black, Anodized Aluminum, AISI 316L Stainless Steel
Lumen Maintenance	90,000 hrs, L90 (Ta 35°C)
Fixture Dimensions	See page 2
IP Rating	IP67
Impact Resistance	IK10

ORDERING INFORMATION


Example: F20112.3.5.02.US. Power Supplies / Accessories ordered separately.

		5		US
Model No.	Finish	CCT	Optics	
F20112 - Round	3 - Anodized Matte Black	5 - RGB+W	02 - Medium 30°	US
F20113 - Square	5 - Anodized Aluminum		05 - Diffused	
	6 - AISI 316L Stainless Steel			


Job Name/Date:

Fixture Type Designation:

FIXTURE DIMENSIONS



FLEA MINI Downlight Round



FLEA MINI Downlight Square


SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00288-P	DMX / RDM (Field Addressable) / DALI	120-277VAC to 24VDC, 100W, Class 2, DRY	1-16

For other power supply options consult factory.

ACCESSORIES



A1006

Honeycomb Screen

Order together with the product

Job Name/Date:

Fixture Type Designation: