


# KRILL TRACK 3.0


Krill Track is a family of low voltage adjustable track lighting with clean lines and compact dimensions for lighting display cases and alcoves in museums and retail environments. It is available with surface mounted or recessed installation flush with the wall or ceiling. Connection accessories enable continuous ceiling-to-wall or wall-to-wall installation, as well as in straight or right-angled lines. It is available in 4 sizes with multiple optics options and 4 standard finishes. Krill Track 3.0 is the Ø1.2" x 1.3", 4.5W version with fixed focus.



## TECHNICAL DATA

<b>Wattage</b>	5.5W
<b>Power Supply</b>	Remote 48VDC power supply, not included.
<b>Dimming</b>	DALI-2 (requires a DALI Master Controller) ON/OFF
<b>Construction</b>	Body: Anticorodal Aluminum Joint: Brass Adapter: Polyamide
<b>CCT</b>	2700K, 3000K, 4000K
<b>CRI</b>	>90
<b>Delivered Lumens</b>	281 lm (3000K, 23°)
<b>Efficacy</b>	51.1 lm/W (3000K, 23°)
<b>Optics</b>	16° , 23° , 33° , 42° , 21°x50° , 50°x21°
<b>Finishes</b>	Track Head: Antique Bronze, Black, Rose Gold, White, Custom RAL on request Track: Black, White available on request
<b>Fixture Dimensions</b>	6.30" x 1.30" x 2.05"
<b>Fixture Weight</b>	0.15 lbs
<b>LED Source</b>	1 High Intensity Power LED
<b>Lumen Maintenance</b>	50,000h L90 B10 (Ta 25°C)
<b>Color Consistency</b>	2-Step MacAdam
<b>Operating Temp.</b>	32°F- 95°F
<b>IP Rating</b>	IP40

Fixture Dimensions



## ORDERING INFORMATION

Example: **KT30301D00F0MZ**. Power Supplies / Accessories / Track ordered separately.

KT3030				
Model No.	Dimming	CCT	Optic	Finish
KT3030	1D00 - DALI-2 1000 - On/Off	F - 2700K 5 - 3000K 9 - 4000K	0S - 16° 0M - 23° 0L - 33° 0K - 42° 0W - 21° x 50° 0X - 50° x 21°	Z - Antique Bronze N - Black Y - Rose Gold B - White

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

48VDC


Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00568</a>	Non-Dim	120-277VAC to 48VDC, 36W, Class 2	1-5
<a href="#">PPLT00576</a>	Non-Dim	120-277VAC to 48VDC, 60W, Class 2	1-8
<a href="#">PPLT00577</a>	Non Dim	120-277VAC to 48VDC, 96W, Class 2	1-13

For other power supply options consult factory.

## ACCESSORIES - Required for Installation




**BE0030005**  
Recessed Track  
3.28 inch (1 m)



**BE0030004**  
Recessed Track  
6.56 inch (2 m)



**BE0030012**  
Surface-mounted Track  
3.28 inch (1 m)




**BE0030025**  
Surface-mounted Track  
6.56 inch (2 m)


## ACCESSORIES - Connectors




**BE0031008**  
Flexible Connector




**BE0030026**  
Straight Connector




**BE0031009**  
Vertical Connector - Ceiling-Wall



**BE003100A**  
Horizontal Connector



## ACCESSORIES - End Caps



**BE0031000**  
End Cap - Surface-mounted track




**BE0031003**  
End cap - Recessed track


Job Name/Date:

Fixture Type Designation:

## ACCESSORIES - Connector Covers




**BE0031006**  
Vertical L-shaped Connector Cover  
Surface-mounted track




**BE0031007**  
Horizontal L-shaped Connector Cover  
Surface-mounted track

## ACCESSORIES - Connector Covers




**BE003100B**  
Concealable Power Supply End Cap




**BE003TE20**  
Power Supply End Cap

## ACCESSORIES - Track Covers




**BE0032005**  
Black Cover for Track - Surface-mounted  
9.84' (3 m)



**BE0032006**  
Black Cover for Track - Recessed  
9.84' (3 m)

## ACCESSORIES - Anti-glare



**WHK130A0**  
Honeycomb Louver



**WBA01E** - White  
**WBA01N** - Black  
**WBA01Y** - Rose Gold  
**WBA01Z** - Antique Bronze  
Standard Snout

Job Name/Date:




Fixture Type Designation:

**PHOTOMETRIC DATA** - Note: All photometric data is 3000K

16°

21°x50°

23°



PHOTOMETRIC FILENAME : KRILL\_TRACK\_3.0\_S\_16\_3000K\_5.5W\_48VDC.IES




PHOTOMETRIC FILENAME : KRILL\_TRACK\_3.0\_W\_21X50\_3000K\_5.5W\_48VDC.IES

PHOTOMETRIC FILENAME : KRILL\_TRACK\_3.0\_M\_23\_3000K\_5.5W\_48VDC.IES

33°

42°

50°x21°



PHOTOMETRIC FILENAME : KRILL\_TRACK\_3.0\_L\_33\_3000K\_5.5W\_48VDC.IES

PHOTOMETRIC FILENAME : KRILL\_TRACK\_3.0\_K\_42\_3000K\_5.5W\_48VDC.IES

PHOTOMETRIC FILENAME : KRILL\_TRACK\_3.0\_X\_50X21\_3000K\_5.5W\_48VDC.IES

Job Name/Date:

Fixture Type Designation: