

# MIDI LINE - Top Light LLTW2


MIDI LINE is an easy to install, bendable LED strip that is IP65/IP68-rated making it ideal for swimming pools or fountains for panel installation in reinforced concrete with tiles or pool liner or indoor/outdoor areas. It is available in Side, Top or Total Light with static white, tunable white or RGB. White PVC outercase and opal resin guarantee protection against UV rays and the corrosive action of salt and sodium hypochlorite. **Not cuttable in the field.**



## TECHNICAL DATA

|                           |   |
|---------------------------|---|
| <b>Wattage</b>            | 12W / 3.28 ft (1 m)   |
| <b>Power Supply</b>       | Remote Fountain/Pool Approved 24VDC Power Supply, not included. See page 2. |
| <b>Construction</b>       | Body: Opal Polyurethane Resin   |
| <b>CCT</b>                | 2900K-5600K (120+120 LED / 3.28')   |
| <b>CRI</b>                | 85  |
| <b>Delivered Lumens</b>   | 680 lm / 3.28'  |
| <b>Efficacy</b>           | 56.7 lm/W   |
| <b>Optics</b>             | 120°  |
| <b>Fixture Dimensions</b> | 0.43" w x 0.39" h x Various Lengths   |
| <b>Bend Radius</b>        | 3.94" - Vertical  |
| <b>LED Source</b>         | SMD 3014  |
| <b>LED Spacing</b>        | 120+120 LED per 3.28 ft (1 m), 0.17" between LEDs                           |
| <b>Lumen Maintenance</b>  | L80, B10>50,000 hrs   |
| <b>Color Consistency</b>  | 2-3-Step MacAdam  |
| <b>Operating Temp</b>     | -22°F to 131°F  |
| <b>IP Rating</b>          | IP65, IP68  |

Fixture Dimensions



**NOT CUTTABLE IN THE FIELD**

**MUST USE SUITABLE APPROVED FOUNTAIN & SWIMMING POOL POWER SUPPLY WHICH IS REMOTELY MOUNTED**

## ORDERING INFORMATION

Example: LLTW2M-24.68.MD.X.US. Power Supplies / Accessories ordered separately.

|  |   |              |   |                        |   |  |   |  |   |           |
|--|---|--------------|---|------------------------|---|--|---|--|---|-----------|
| LLTW2M   | - | 24           | . |                        | . | MD   | . |  | . | US        |
| <b>Model No.</b>   |   | <b>Power</b> |   | <b>IP Rating</b>       |   | <b>Cable Exit</b>                              |   |  |   | <b>US</b> |
| LLTW2M - 120+120 LED / 3.28' (1 m)   |   | 24 - 24VDC   |   | 65 - IP65<br>68 - IP68 |   | X - End Feed<br>Y - Side Feed<br>Z - Back Feed |   |  |   | US        |
| <p><b>NOTE:</b> Available in lengths up to 75 feet. Please specify length when ordering.</p> |   |              |   |                        |   |  |   |  |   |           |

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

24VDC - **TO BE USED WITH FOUNTAIN / SWIMMING POOLS**

| Part Number                   | Description                                       | Input/Output                                      | # of Fixtures |
|-------------------------------|---|---|---------------|
| <a href="#">FPV-100000024</a> | Non-Dim   | 120-277VAC to 24VDC, 100W, Class 2, IP66, NEMA 4X | 1-6           |
| <a href="#">FPV-100100024</a> | 0-10V Dimming (2 Channels)                        | 120-277VAC to 24VDC, 100W, Class 2, IP66, NEMA 4X | 1-12          |
| <a href="#">FPV-100EL0024</a> | DMX / RDM (Field Addressable) / DALI (4 Channels) | 120-277VAC to 24VDC, 100W, Class 2, IP66, NEMA 4X | 1-4           |

## DRIVERS IN NEMA 4X ENCLOSURE - **FOR INDOOR/OUTDOOR USE ONLY**

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

| Part Number               | Description                         | Input/Output                                | # of Fixtures |
|---------------------------|-------------------------------------|---|---------------|
| <a href="#">PPLT00715</a> | ELV / TRIAC / 0-10V Dimming to 0.1% | 120-277VAC to 24VDC, 96W, Class 2, WET/DAMP | 1-6           |

## Suggested Lutron Compatible - **FOR INDOOR/OUTDOOR USE ONLY**


| Part Number               | Option         | Lutron SKU | Dim Range | Description                                    | Input/Output                      | # of Fixtures |
|---------------------------|----------------|------------|-----------|--|-----------------------------------|---------------|
| <a href="#">PPLT00273</a> | L3DAE / L3DA3W | L3DA       | 100%-1%   | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 24VDC, 40W, Class 2 | 1-2           |
| <a href="#">PPLT00530</a> | L3DAE / L3DA3W | L3DA       | 100%-1%   | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 24VDC, 96W, Class 2 | 1-6           |

For other power supply options consult factory.

Job Name/Date:


Fixture Type Designation:

## ACCESSORIES - Installation / Mounting



| Code   | Finishing               | Description                                      |
|--|-------------------------|--|
| <b>PRO-AL-10x11-AL</b>                         | Aluminum                | Rigid guide L max 9.84 ft                        |
| <b>OUT-S-10x11.W</b><br><b>OUT-S-10x11.F</b>   | White<br>Opal           | Silicone profile                                 |
| <b>CLIP-S-10x11.W</b><br><b>CLIP-S-10x11.F</b> | White<br>Opal           | Silicone clip                                    |
| <b>CLIP-AC-9.5x6.5-AC</b>                      | AISI 304 harmonic steel | Steel clip                                       |
| <b>SNK-AC-10x11-AC</b>                         | AISI 316 harmonic steel | Flexible profile L max 3.28 ft                   |
| <b>SNK2-AC-10x11-AC</b>                        | AISI 316 harmonic steel | Flexible profile for false ceiling L max 3.28 ft |
| <b>PRO-AC-10x11-AC</b>                         | AISI 316 harmonic steel | Rigid guide L max 8.20 ft                        |

## POWER CABLE EXIT / AREA WITH REDUCED LIGHT



Job Name/Date:

Fixture Type Designation: