

Nothing

D

OTHER AVAILABLE CODES

TECHNICAL FEATURES | LIGHT SOURCE

Code Downlight 90° I Wall recessed 90° Type Material Absorption capacity* Weight Mounting IP20 IP rating Control gear Constant voltage driver (not included) Cut out for plasterboard Lamp type **=** Lamp wattage $1 \times 21W$ Luminous efficacy 1 × 2100 lm - 3000K Light distribution Wide beam 120° Fitting Light color White 3000K Light hole Voltage connection By driver (optional)

Other available light colors: 2700K.

CRI




Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710





-	30.31"	
-	31.50"	

TECHNICAL FEATURES | BODYFRAME

Code BU9010.00

Downlight 90° I Wall recessed 90° Type

Material 00: Coral® 7.72 lbs Weight Mounting Ceiling recessed

IP rating Insulation class

Control gear

Cut out for plasterboard (31.50 in for each module installed + 6.30 in) \times 5.51 in

Lamp type

Lamp wattage Luminous efficacy Light distribution Fitting

Light color

Light hole (31.50 in for each module installed)

Voltage connection CRI

Must be installed for multiples of 31.50 in Note

and cannot be cut.




Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710 Fax: (908) 996-7042

Outdoor Recessed





3.15"

TECHNICAL FEATURES | CLOSURE HEADPARTS

Code BU9014.00 Material 00: Coral® 2.65 lbs (couple) Weight Mounting Wall and ceiling recessed IP rating

Cut out for plasterboard 5.51×3.35 in

Note

You need two headparts delivered as couple with a unique code 9014.00 to close a continuous line of the NOTHING product (code 9010.00 / 9013.00).



2.76"

TECHNICAL FEATURES | PROTECTION SHIELD

Code	9011.08	9011.16	9011.24	9011.32
Material	Satin polycarbonate	Satin polycarbonate	Satin polycarbonate	Satin polycarbonate
Dimensions	$800 \times 70 \text{ mm}$	1600 × 70 mm	2400 × 70 mm	$3200 \times 70 \text{ mm}$
Note	-	-	-	-

 $^{^{\}circ}$ The absorption capacity per ft^{3} calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of $8.86\ ft$ in height and therefore expressed in ft^{2}