

EGO / EGO MAXI RGBW Floodlight

EGO and EGO MAXI RGBW Floodlights are round projectors in 2 sizes, with a marine grade stainless steel 316L housing (galvanized treatment on request) making it suitable for a variety of outdoor installations. They are available in RGB+W and 4 optics options.



EGO



EGO MAXI

Fixture Dimensions - see page 2

TECHNICAL DATA

Wattage	12W (EGO), 36W (EGO MAXI)
Power Supply	Remote 24VDC, not included. See page 2.
Construction	Housing: Marine Grade Stainless Steel 316L Lens: Extra Clear Tempered Glass
CCT	RGB+W
CRI	>80
Delivered Lumens	EGO - 253 lm: (R) 33, (G) 84, (B) 20, (W) 116 (6500K) EGO MAXI - 759 lm: (R) 100, (G) 251, (B) 61, (W) 347 (6500K)
Efficacy	21.1 lm/W (EGO / EGO MAXI)
Optics	10°, 25° 45°, 10°x40°
Finishes	Stainless Steel ASIS 316L
Lumen Maintenance	90,000 hrs (Ta 35°C)
Fixture Dimensions	Ø4.53" x 4.72" x 6.46" h (EGO) Ø7.13" x 5.87" x 9.76" h (EGO MAXI)
IP Rating	IP67
Impact Resistance	IK07

ORDERING INFORMATION


Example: F40404.6.5.36.US. Power Supplies / Accessories ordered separately.

	6	5		.US
Model No.	Finish	CCT	Optics	
F40404 - EGO	6 - ASIS 316L Stainless Steel	5 - RGB+W	01 - 10° Spot	.US
F40425 - EGO MAXI			36 - 25° Medium	
			32 - 45° Wide	
			38 - 10° x 40°	

Job Name/Date:

Fixture Type Designation:

FIXTURE DIMENSIONS



SUGGESTED POWER SUPPLIES



24VDC

Part Number	Description	Input/Output	# of Fixtures	
			12W	32W
PPLT00288-P	DMX / RDM (Field Addressable) / DALI	120-277VAC to 24VDC, 100W, Class 2	1-6	1-2

For other power supply options consult factory.


ACCESSORIES

Installation / Anti-Glare



ACCESSORIES

Controllers (RGBW)



PPWD00570 - RGBW DMX512+Wifi Controller

Touch Sensitive
Can be controlled by WiFi
Controls 3 zones synchronously and separately

Job Name/Date:

Fixture Type Designation: