

FLEXBAR



Score: 2.6
 This product has been certified as having 'Excellent' circularity in accordance with the LIA/CIBSE Assured Product Verification Scheme.

TECHNICAL DATA

		Downlight Only 4.59 ft —		Downlight Only 9.19 ft —		Downlight Only Corner L	
100%		LED WATTAGE	LUMEN OUTPUT	LED WATTAGE	LUMEN OUTPUT	LED WATTAGE	LUMEN OUTPUT
	LED WATTAGE PER METER						
WHITE	6	8	1460	16	2920	8	1460
	10	14	2360	27	4720	14	2360
	14	20	3350	39	6700	20	3350
	22	31	5090	63	10180	31	5090
METALLIZED	6	8	1525	16	3050	8	1525
	10	14	2470	27	4940	14	2470
	14	20	3505	39	7010	20	3505
	22	31	5325	63	10650	31	5325
BLACK	6	8	1195	16	2390	8	1195
	10	14	1930	27	3860	14	1930
	14	20	2740	39	5480	20	2740
	22	31	4165	63	8330	31	4165

		Up and Downlight 4.59 ft —		Up and Downlight 9.19 ft —		Up and Downlight Corner L	
20% 80%		LED WATTAGE	LUMEN OUTPUT	LED WATTAGE	LUMEN OUTPUT	LED WATTAGE	LUMEN OUTPUT
	LED WATTAGE PER METER						
WHITE	6	8	1450	16	2900	8	1450
	10	14	2350	27	4700	14	2350
	14	20	3345	39	6690	20	3345
	22	31	5105	63	10210	31	5105
METALLIZED	6	8	1525	16	3050	8	1525
	10	14	2470	27	4940	14	2470
	14	20	3510	39	7020	20	3510
	22	31	5355	63	10710	31	5355
BLACK	6	8	1240	16	2480	8	1240
	10	14	2010	27	4020	14	2010
	14	20	2860	39	5720	20	2860
	22	31	4365	63	8730	31	4365