# **GORGET WALL 1**



datasheet





SILVER



Fixture Dimensions - see page 2

# TECHNICAL DATA

captivate attention.

Wattage / Input	15W (600mA)		
Power Supply	Remote, not included. See page 2		
Construction	Body: High Impact Polystyrene / PMMA		
	Lens: Satin Diffuser		
ССТ	2700K, 3000K, 4000K		
CRI	>90		
Delivered Lumens	1935 lm (3000K)		
Efficacy	129 lm/W (3000K)		
Optics	Indirect		
Lumen Maintenance	50,000 hrs L80, B10 (Ta 25°C)		
Color Consistency	3-Step MacAdam		
Finishes	14 Standard - see below and page 2 for chart		
Fixture Dimensions	26.61" l x 33.66" h x 0.94" w		
IP Rating	IP20		

Gorget, designed by Karim Rashid, is a series of sleek, futuristic luminaires rooted in modular elements that come together to form the collection of three styles. Constellation is composed of interlocking rings that can be woven into captivating hanging sculptures, Linear is a system ideal for accentuating corridors and hallways, and Wall is a sconce to adorn surfaces. Gorget Wall 1 is the smaller 15W wall version, and comes in a variety of original finishes to

## **ORDERING INFORMATION**

Example: IO5.402.01L1.1.561.B0.US. Power Supplies sold separately.

IO5.4021.01L1	. 1				.us
Model No.	Power-Dimming	ССТ	Finish		
IO5.4021.01L1	1 - Remote	<b>561</b> - 2700K	<b>B0</b> - Classic Black	I0 - Night	.US
		<b>661</b> - 3000K	W0 - Cream White	<b>H0</b> - Dark Honey	
		<b>761</b> - 4000K	<b>T0</b> - Titan	<b>E0</b> - White Gold	
			S0 - Silver	<b>L0</b> - Light Gold	
			<b>D0</b> - Deep Green	<b>G0</b> - Gold	
			O0 - Ocean	C0 - Cooper	
			R0 - Royal Red	P0 - Karim Pink	

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

1 of 2




datasheet

#### **FIXTURE DIMENSIONS**



#### PHOTOMETRIC DATA

Note: All photometry is 3000K



PHOTOMETRIC FILENAME: GORGET\_WALL\_1\_3000K\_34.8IN\_REPAIRED.IES

#### **FINISHES**



## **SUGGESTED POWER SUPPLIES**

600mA

OOOTIA .						
Part Number Description		Input/Output	# of Fixtures			
PPLT00308-P	0-10V Dimming to 0.1%	120-277VAC to 600mA, 30W, Class 2, DAMP	1-1			
PPLT00467-P	0-10V Dimming to 1.0%	120-277VAC to 600mA, 50W, Class 2, DAMP	1-1			
PPLT00655-P	0-10V Dimming to Dark	120-277VAC to 600mA, 50W, Class 2, IP20	1-1			
PPLT00558-P	0-10V Dimming to 0.1%	120-277VAC to 600mA, 75W, Class 2	1-1			

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation: