

Ottonote LED is a series of bulbs on a string made of neoprene wire and installed with 8 steel hooks. The bulbs comes with a transparent decorative glass lens and a diameter of 3.5" available in 2 color temperatures with a black finish at the connection to the wire.

## TECHNICAL DATA

<b>Wattage</b>	4.5W
<b>Power Supply</b>	Remote 12VDC, not included. See page 2
<b>Construction</b>	Body: Neoprene Plastic, Steel Hooks Lens: Transparent Decorative Glass
<b>CCT</b>	2700K, 3000K
<b>CRI</b>	>80
<b>Delivered Lumens</b>	450 lm (2700K) 470 lm (3000K)
<b>Efficacy</b>	100 lm/W (2700K) 104.4 lm/W (3000K)
<b>Optics</b>	Narrow
<b>LED Source</b>	Modulo LED
<b>Finishes</b>	Black
<b>Fixture Dimensions</b>	String: 32.81 ft with 8 bulbs / hooks
<b>IP Rating</b>	IP66



Fixture Dimensions  
String Length: 32.8 ft



## ORDERING INFORMATION

Example: R10.012.LED.2.2.US. Power supplies ordered separately

R10.012.LED	.	2	.	US
<b>Model No.</b>	<b>CCT</b>	<b>Body Finish</b>		
R10.012.LED	2 - 2700K 3 - 3000K	2 - Black	US	

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

12VDC

Part Number	Description	Input/Output	# of Fixtures
<a href="#"><u>PPLT00654</u></a>	0-10V Dimming	120-277VAC to 12VDC, 50W, Class 2	1-1
<a href="#"><u>PPLT00506</u></a>	Non-Dim	120-277VAC to 12VDC, 60W, Class 2, DAMP	1-1
<a href="#"><u>PPLT00721</u></a>	ELV/TRIAC & 0-10V to 0.1%	120-277VAC to 12VDC, 100W, Class 2, WET/DAMP	1-2

For other power supply options consult factory.

## PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: