

KOS WALL ASYMMETRIC


KOS is a family of versatile, small boxlike fixtures that comes as a recessed downlight, in-grade uplight, wall mounted, or floodlight for installation in outdoor environments. KOS Wall Asymmetric is a recessed wall version with asymmetric optics available in 3 color temperatures and 3 standard finishes.



TECHNICAL DATA

Wattage	10W
Power Supply	Remote 500mA, not included. See page 2
Construction	Housing: Anticorodal Aluminum Lens: Extra Clear Tempered Glass
CCT	2700K, 3000K, 4000K
CRI	>80
BUG Rating	B0-U4-G0 (3000K)
Delivered Lumens	560 lm (3000K)
Efficacy	56 lm/W (3000K)
Optics	Asymmetric
Finishes	Anthracite, ALU Gray (RAL9006), AISI 316L Stainless Steel
Lumen Maintenance	90,000 hrs, L90 (Ta 35°C)
Fixture Dimensions	4.33" l x 4.33" w x 4.17" depth
IP Rating	IP67, IP68 Quick Connection
Impact Resistance	IK08

Fixture Dimensions



BACKBOX INCLUDED

ORDERING INFORMATION

Example: F10506.1.2.06.US. Power Supplies ordered separately. Backbox included.

F10506			06	US
Model No.	Finish	CCT	Optics	
F10506	1 - Anthracite 4 - ALU Gray (RAL9006) 6 - AISI 316L Stainless Steel	2 - 2700K 3 - 3000K 4 - 4000K	06 - Asymmetrical	US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

500mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00466-P	0-10V Dimming to 1.0%	120-277VAC to 500mA, 10W, Class 2, DAMP	1-1
PPLT00497	Phase Dim (120V only)	120VAC to 500mA, 12W, Class 2, DAMP	1-1
PPLT00262	Leading / Trailing Edge Phase Dimming to 10% (120V only)	120-277VAC to 500mA, 32W, Class 2	2-3
PPLT00467-P	0-10V Dimming to 1.0%	120-277VAC to 500mA, 50W, Class 2, DAMP	1-4
PPLT00561-P	0-10V Dimming to 0.1%	120-277VAC to 500mA, 100W, Class 2	1-4

Suggested Lutron Compatible


Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00259	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA, 10W, Class 2	1-1
PPLT00676	PEQOE	PEQ0	100%-0.1%	Hi-Lume™ Premier 0.1% EcoSystem™ F2B	120-277VAC to 500mA, 20W, Class 2	1-2

For other power supply options consult factory.

PHOTOMETRIC DATA

Note: All photometry is 3000K

Maximum Candela = 541.6



PHOTOMETRIC FILENAME : KOS WALL ASYM 30K - 10506.X.3.06.IES

Job Name/Date:

Fixture Type Designation: