


C2-STT-D is an LED spotlight with a triple lens for installation on Multisystem EVO track. It is suitable for showcase lighting in museum and retail settings, with 360° rotatable, 90° swiveling, 5 color temperatures, 4 optics options and aluminum anodized in matte black or powder-coated in white RAL 9016.



## TECHNICAL DATA

<b>Wattage</b>	9W
<b>Power Supply</b>	Remote 48VDC, not included. See page 2
<b>Dimming</b>	0-10V, DALI, or Casambi
<b>Construction</b>	Body: Anodized Aluminum
<b>CCT</b>	2700K, 3000K, 3500K, 4000K, 5700K
<b>CRI</b>	>97
<b>Delivered Lumens</b>	630 lm (3000K, 25°)
<b>Efficacy</b>	70 lm/W (3000K, 25°)
<b>Optics</b>	18°, 25°, 32°, 67° <i>Light diffusion foil included</i>
<b>Finishes</b>	Anodized Matte Black Powder-coated White RAL9016
<b>Fixture Dimensions</b>	Ø1.54" x 5.24" l (head) 6.54" l x 0.64" w x 0.71" h (base)
<b>Lumen Maintenance</b>	L80,B10 >50,000hrs
<b>IP Rating</b>	IP20

Fixture Dimensions



**NOTE: Track to be ordered separately**

## ORDERING INFORMATION

Example: C2-STT-D-40-2-SW. Accessories / Power Supplies ordered separately.

C2-STT-D	-		-		-	
----------	---	--	---	--	---	--

Model No.	CCT	Optics	Finish
C2-STT-D (A400463)	27 - 2700K	T8 - 18° lens**	SW - Anodized Black
	30 - 3000K	T5 - 25° lens	W - White RAL9016
	35 - 3500K	T2 - 32° lens	
	40 - 4000K	T7 - 67° lens	
	57 - 5700K	** GLASS LENS – WITH LIGHT DIFFUSION FOIL, SEE ACCESSORIES PAGE	

Job Name/Date:

Fixture Type Designation:

## ACCESSORIES




**Honeycomb Grid**  
A000603



**Anti-Glare Tube**  
A300171-\_\_  
SW - Black  
W - White



**Inclined Tube**  
A300172-\_\_  
SW - Black



**\*\*18° Glass Lens**  
A000530-S  
With Light Diffusion Foil



**Barn Door**  
A300148-\_\_  
SW - Black

## SUGGESTED POWER SUPPLIES

48VDC

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00574</a>	Non-Dim	120-277VAC to 48VDC, 30W, Class 2	1-2
<a href="#">PPLT00646</a>	0-10V Dimming	120-277VAC to 48VDC, 30W, Class 2	1-2
<a href="#">PPLT00568</a>	Non-Dim	120-277VAC to 48VDC, 36W, Class 2	1-3
<a href="#">PPLT00648</a>	0-10V Dimming	120-277VAC to 48VDC, 60W, Class 2	1-5
<a href="#">PPLT00665</a>	ELV / TRIAC & 0-10V dimming (100 to 0%)	120-277VAC to 48VDC, 96W, Class 2	1-8



For other power supply options consult factory.

Job Name/Date:


Fixture Type Designation:

## PHOTOMETRIC DATA - Triple Lens

for light color ~3000K | standard lens 25° | 1000mA | CRI typ. 97, R9 > 90, R12 > 90 | color variation ≤ 3 SDCM



Maximum Candela = 3244.7



PHOTOMETRIC FILENAME : C2-STT (TRIPPLE LENS 25 DEGREE) 10W.IES

Job Name/Date:

Fixture Type Designation: