


DIAGONAL 14

Diagonal 14 is a recessed angled linear profile offering reduced glare that is suitable for indoor installation under cabinets, shelving or other furniture. With a body made of aluminum, it comes in 4 lengths (39.4", 78.7", 118.1" or 159.5") and 4 standard finishes.



TECHNICAL DATA

Wattage	18W per 3.28 ft (1 m)
Power Supply	Remote 24VDC, not included. See page 2
Construction	Body: Aluminum
CCT	2700K, 3000K, 3500K, 4000K
CRI	85
Delivered Lumens	2034 lm per 3.28 feet (3000K)
Efficacy	113 lm/W
Optics	LED Tape, Field Cuttable (See page 2)
Finish	White Painted, Anodized, Black Anodized, Raw Aluminum
Fixture Dimensions	Length: 39.37", 78.74", 118.11", or 159.45" MAX LED Width: 0.55"
IP Rating	IP20



Profile without LED Tape

Fixture Dimensions



ORDERING INFORMATION


Example: H5010001.US. LED Tape / Accessories sold separately.

H5			.US
Model No.	Length	Finish	
H5	0100 - 39.37"	00 - Raw Aluminum	.US
	0200 - 78.74"	01 - White Painted	
	0900 - 118.11"	20 - Anodized	
	1200 - 159.45"	21 - Black Anodized	

Job Name/Date:

Fixture Type Designation:

FINISHES



White Painted



Anodized



Black Anodized




Raw Aluminum



LED TAPE

24VDC - Field Cuttable



16.40' l x 0.4" w

PPLL00622 – 2700K

PPLL00623 – 3000K

PPLL00624 – 3500K

PPLL00625 – 4000K

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00481	Non-Dim	120-277VAC to 24VDC, 24W, Class 2	1-1
PPLT00690	ELV / TRIAC & 0-10V Dimming	120-277VAC to 24VDC, 40W, Class 2, IP67	1-1
PPLT00691	Non-Dim	120-277VAC to 24VDC, 60W, Class 2, IP67	1-2
PPLT00709	ELV / TRIAC & 0-10V to 5% and OFF	120-277VAC to 24VDC, 96W, Class 2, DAMP	1-4
PPLT00158	Non-Dim	120VAC to 24VDC, 100W, Class 2	1-4
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-4

Suggested Lutron Compatible


Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00273	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 40W, Class 2	1-1
PPLT00530	L3D0E / L3D03W	L3D0	100% to 0.1%	Hi-Lume™ Premier 0.1% EcoSystem™ or 3-Wire LED F2B Driver	120-277VAC to 24VDC, 96W, Class 2	1-4

For other power supply options consult factory.


Job Name/Date:

Fixture Type Designation:


ACCESSORIES – End cap with hole




H5999901
End Cap with Hole
White



H5999940
End Cap with Hole
Silver



H5999902
End Cap with Hole
Black





H5999922
End Cap with Hole
Gray


Mounting Plate




F - Click Cover
A2060016 - Transparent
A2060038 - Opal
A2060041 - Black



Y - Flexible Mounting Plate
A2090019 - Inox Stainless Steel



Cone Y - Mounting Plate
A2130019 - Inox Stainless Steel



T - Mounting Plate
C6960000 - Raw Aluminum

Job Name/Date:

Fixture Type Designation: