


# DIAGONAL 14

Diagonal 14 is a recessed angled linear profile offering reduced glare that is suitable for indoor installation under cabinets, shelving or other furniture. With a body made of aluminum, it comes in 4 lengths (39.4", 78.7", 118.1" or 159.5") and 4 standard finishes.



## TECHNICAL DATA

Wattage	18W per 3.28 ft (1 m)
Power Supply	Remote 24VDC, not included. See page 2
Construction	Body: Aluminum
CCT	2700K, 3000K, 3500K, 4000K
CRI	85
Delivered Lumens	2034 lm per 3.28 feet (3000K)
Efficacy	113 lm/W
Optics	LED Tape, Field Cuttable (See page 2)
Finish	White Painted, Anodized, Black Anodized, Raw Aluminum
Fixture Dimensions	Length: 39.37", 78.74", 118.11", or 159.45" MAX LED Width: 0.55"
IP Rating	IP20



Profile without LED Tape

## Fixture Dimensions



## ORDERING INFORMATION


Example: H5010001.US. LED Tape / Accessories sold separately.

H5			.US
Model No.	Length	Finish	
H5	0100 - 39.37"	00 - Raw Aluminum	.US
	0200 - 78.74"	01 - White Painted	
	0900 - 118.11"	20 - Anodized	
	1200 - 159.45"	21 - Black Anodized	

Job Name/Date:

Fixture Type Designation:

## FINISHES




White Painted



Anodized



Black Anodized




Raw Aluminum



## LED TAPE

24VDC - Field Cuttable



16.40' l x 0.4" w

**PPLL00622** – 2700K

**PPLL00623** – 3000K

**PPLL00624** – 3500K

**PPLL00625** – 4000K

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00158</a>	Non-Dim	120VAC to 24VDC, 100W, Class 2	1-4
<a href="#">PPLT00543</a>	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-4

## Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
<a href="#">PPLT00530</a>	L3D0E / L3D03W	L3D0	100% to 0.1%	Hi-Lume™ Premier 0.1% EcoSystem™ or 3-Wire LED F2B Driver	120-277VAC to 24VDC, 96W, Class 2	1-4

## DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715


Part Number	Description	Input/Output	# of Fixtures 18W
<a href="#">PPLT00715</a>	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-4

For other power supply options consult factory.


Job Name/Date:

Fixture Type Designation:


## ACCESSORIES – End cap with hole




**H5999901**  
End Cap with Hole  
White



**H5999940**  
End Cap with Hole  
Silver



**H5999902**  
End Cap with Hole  
Black





**H5999922**  
End Cap with Hole  
Gray


## Mounting Plate




**F - Click Cover**  
**A2060016** - Transparent  
**A2060038** - Opal  
**A2060041** - Black



**Y - Flexible Mounting Plate**  
**A2090019** - Inox Stainless Steel



**Cone Y - Mounting Plate**  
**A2130019** - Inox Stainless Steel



**T - Mounting Plate**  
**C6960000** - Raw Aluminum

Job Name/Date:

Fixture Type Designation: