

DIAGONAL 14


designplan®

datasheet

Diagonal 14 is a recessed angled linear profile offering reduced glare that is suitable for indoor installation under cabinets, shelving or other furniture. With a body made of aluminum, it comes in 4 lengths (39.4", 78.7", 118.1" or 159.5") and 4 standard finishes.

TECHNICAL DATA

Wattage	18W per 3.28 ft (1 m)
Power Supply	Remote 24VDC, not included. See page 2
Construction	Body: Aluminum
CCT	2700K, 3000K, 3500K, 4000K
CRI	85
Delivered Lumens	2034 lm per 3.28 feet (3000K)
Efficacy	113 lm/W
Optics	LED Tape, Field Cuttable (See page 2)
Finish	White Painted, Anodized, Black Anodized, Raw Aluminum
Fixture Dimensions	Length: 39.37", 78.74", 118.11", or 159.45" MAX LED Width: 0.55"
IP Rating	IP20





Profile without LED Tape

ORDERING INFORMATION

Example: H5010001.US. LED Tape / Accessories sold separately.

H5			.US
Model No.	Length	Finish	
H5	0100 - 39.37"	00 - Raw Aluminum	
	0200 - 78.74"	01 - White Painted	
	0900 - 118.11"	20 - Anodized	
	1200 - 159.45"	21 - Black Anodized	

Fixture Dimensions



Job Name/Date:

Fixture Type Designation:

FINISHES



White Painted


Anodized

Black Anodized

Raw Aluminum

LED TAPE

24VDC - Field Cuttable

**PPLL00622** – 2700K**PPLL00623** – 3000K**PPLL00624** – 3500K**PPLL00625** – 4000K

16.40' l x 0.4" w

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00284	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, DAMP	1-4
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-4

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3D0E / L3D03W	L3D0	100% to 0.1%	Hi-Lume™ Premier 0.1% EcoSystem™ or 3-Wire LED F2B Driver	120-277VAC to 24VDC, 96W, Class 2	1-4

DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures 18W
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-4

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:

ACCESSORIES – End cap with hole



H5999901
End Cap with Hole
White



H5999940
End Cap with Hole
Silver




H5999902
End Cap with Hole
Black





H5999922
End Cap with Hole
Gray


Mounting Plate




F - Click Cover
A2060016 - Transparent
A2060038 - Opal
A2060041 - Black



Y - Flexible Mounting Plate
A2090019 - Inox Stainless Steel



Cone Y - Mounting Plate
A2130019 - Inox Stainless Steel



T - Mounting Plate
C6960000 - Raw Aluminum

Job Name/Date:

Fixture Type Designation: