

DRIVE LINE (L110X)

Drive Line L110X is a linear or curved IP67-rated LED luminaire, made in AISI 316L stainless steel, for flush installation on floors in indoor or outdoor areas. It is driveover rated, and available with custom curvatures to follow every project. It is available in static or tunable white, and RGBW color temperatures, diffused optics, and a color rendering index of >90. **Not cuttable in the field.**



Fixture Dimensions
Image coming soon

TECHNICAL DATA

Wattage	22 W per 3.3 ft (1m) - Static White 24 W per 3.3 ft (1m) - Tunable White 36W per 3.3 ft (1m) - RGBW
Power Supply	Remote 24VDC, not included. See page 2.
Construction	Body: AISI 316L Stainless Steel Lens / Diffuser: Opal Polyurethane Resin Cable Length: 39.4" (2x0.5mm2) included
CCT	2200K, 2500K, 2700K, 3000K, 4000K 2700K-6000K Tunable White, RGBW
CRI	>90
Delivered Lumens	1560 lm / 3.28' (3000K) 1900 lm / 3.28' (Tunable White) 1600 lm / 3.28' (RGBW)
Efficacy	70.9 lm/W per 3.28' (3000K) 79.2 lm/W per 3.28' (Tunable White) 44.4 lm/W per 3.28' (RGBW)
Optics	Diffuse
Fixture Dimensions	1.97" x 1.06" h x Various Lengths/Curvatures
Bend Radius	
LED Source	SMD 3014 SHINEON SMD 5050 PROLIGHT - RGBW
LED Spacing	408 LED per 3.28 ft (1 m)
Lumen Maintenance	L80, B10>50,000 hrs
Color Consistency	3-Step MacAdam
Operating Temp	-22°F to 131°F
IP Rating	IP67
Impact Resistance	IK10

NOT CUTTABLE IN THE FIELD

ORDERING INFORMATION

Example: L110X-2x10.V5.24.67.F.US. Power Supplies / Accessories ordered separately.

L110X	-		.	24	.	67	.	F	.	US
Model No.	CCT	Power	IP Rating							
L110X - Drive Line	2x10.V8 - 2200K 2x10.V2 - 2500K 2x10.V5 - 2700K 2x10.V - 3000K 2x10.W5 - 4000K	24 - 24VDC	67 - IP67	F	US					
	2xTW8 - 2700K-6000K 2xRGB4W - RGBW									


Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES


24VDC - Consult Factory

ACCESSORIES - Installation




SP-CA-68-2-1 (Static White)

Water immersion / Outdoor power cable
IP68, Black (2x0.50mm²+ n. 2 Kevlar wires)
External Ø0.21".



SP-CA-68-4-1 (Tunable White)

Water immersion / Outdoor power cable
IP68, Black (4x0.50mm²+ n. 2 Kevlar wires)
External Ø0.23".



SP-CA-68-5-1 (RGBW)

Water immersion / Outdoor power cable
IP68, Black (5x0.50mm²+ n. 2 Kevlar wires)
External Ø0.24".

Job Name/Date:

Fixture Type Designation:

PHOTOMETRIC DATA

2200K

3000K

4000K

Job Name/Date:

Fixture Type Designation: