

TECHNICAL CATALOGUE 2024

designplan[®] 

STRAL

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042



Inox Natural



Inox Graphite



Inox Bronze

CRI>80


IP66

IP67


IK09




Recessed wall and floor fixture in AISI 316L stainless steel, including the in-ground embedded part, in both square and circular versions. It provides diffuse illumination. Color temperatures of 2700K, 3000K, and 4000K. Plexiglass diffuser. Installation through flush casing with AISI 316L stainless steel frame in HCT finish available in three colors. Walk-over safe. Casing as accessory for in-ground or concrete installation, accessorized with bottom cap and plaster guard cap. Remote power supply. Surface finish HCT available in three variants.



Emission



Color		
2700 K	3000 K	4000 K
463 lm	463 lm	554 lm
Power		
5 W		




Accessories

IP66

IP67

IK09


lm



CASING
Ø1.97" H: 4.72"
PT51800 N/G/B



BOTTOM CAP
H: 4.72"
PT40004





CASING
Ø1.97" H: 7.68"
PT51801 N/G/B



BOTTOM CAP
H: 7.68"
PT40003




MORTAR CAP
Ø1.97"
PT40006



Emission



Color		
2700 K	3000 K	4000 K
631 lm	631 lm	755 lm
Power		
7 W		




Accessories

IP66

IP67

IK09


lm



CASING
Ø3.15" H: 4.72"
PT51900 N/G/B



BOTTOM CAP
H: 4.72"
PT40004





CASING
Ø3.15" H: 7.68"
PT51901 N/G/B




BOTTOM CAP
H: 7.68"
PT40003




MORTAR CAP
Ø3.15"
PT40007



Emission




Color		
2700 K	3000 K	4000 K
463 lm	463 lm	554 lm
Power		
5 W		



Accessories


IP66 IP67 IK09  lm



CASING
1.97"x1.97" H: 4.72"
PT51810 N/G/B



BOTTOM CAP
H: 4.72"
PT40004





CASING
1.97"x1.97" H: 7.68"
PT51811 N/G/B




BOTTOM CAP
H: 7.68"
PT40003



MORTAR CAP
1.97"x1.97"
PT40008




Emission



Color		
2700 K	3000 K	4000 K
631 lm	631 lm	755 lm

Power		
7 W		




Accessories

IP66

IP67

IK09


lm



CASING
3.15"x3.15" H: 4.72"
PT51910 N/G/B




BOTTOM CAP
H: 4.72"
PT40004



CASING
3.15"x3.15" H: 7.68"
PT51911 N/G/B



BOTTOM CAP
H: 7.68"
PT40003



MORTAR CAP
3.15"x3.15"
PT40009