



Ø0.63"

5.91"

## **Pixel**

VIO.

## OTHER AVAILABLE CODES

BU1007.AC 4 R	_ M _ WD	light color	
		27	2700K
		30	3000K
		40	4000K (on request)
		lens	
		15	15°
		25	25° (on request)
		45	45° (on request)
example of code composition		BU1007.AC 4 R 25 E 30 WD	

## **TECHNICAL FEATURES**

Code
Type

Downlight 90°

AC: AirCoral®
Absorption capacity\*

Weight
Mounting
IP rating

BU1007 XX
Downlight 90°

AC: AirCoral®
14.96 ft² (1.39 m²)

Ceiling recessed
IP40

Control gear Remote constant current driver (not included)

Cut out for plasterboard 5.91 × 5.91 in

Lamp type LED 700mA

Light color White 3000K

White 2700K I 4000K (on request)


Light hole Ø 0.63 in

Voltage connection By driver (optional)

CRI

## OPTIONAL

Brick box cod. BR1007LT





79 Trenton Avenue Frenchtown, NJ 08825

www.designplan.com

el: (908) 996-7710 ax: (908) 996-7042

<sup>\*</sup> The absorption capacity per  $ft^3$  calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 8.86~ft in height and therefore expressed in  $ft^2$