


Candle is a long thin cylindrical wall mounted luminaire made of aluminum or brass with a frosted plexiglass diffuser and a steel or brass canopy. It is available with 3W of power in 3 color temperatures and 4 standard finishes.



TECHNICAL DATA

Wattage	3W
Power Supply	Remote 350mA, not included. See page 2.
Light Source	COB LED
Construction	Body: Aluminum or Brass Canopy: Steel or Brass Lens: Frosted Plexiglass
CCT	2200K, 2700K, 3000K
CRI	80, 90
Delivered Lumens	235 lm (2200K, CRI 90) 350 lm (2700K, CRI 90) 375 lm (3000K, CRI 90)
Efficacy	78.3 lm/W (2200K) 116.7 lm/W (2700K) 125 lm/W (3000K)
Optics	15°-25°
Finishes	4 Standard Body, See Below 2 Standard Details, See Below
Fixture Dimensions	3.94" x 5.12" x 17.72" h
IP Rating	IP20

Fixture dimensions



ORDERING INFORMATION

Example: R70.105.7.ONS.27.US.

R70.105	.		.		.		.	US
Model No.		Body Finish		Detail Finish		CCT		
R70.105		7 - Iron Painted ON - Natural Brass ONS - Brushed Brass ONB - Burnished Brass		ONS - Brushed Brass ONB - Burnished Brass		20 - 2000K 27 - 2700K 30 - 3000K		US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00496	Phase Dim (120V only)	120VAC to 350mA, 12W, Class 2, DAMP	1-2
PPLT00211	Non-Dim	120VAC to 350mA, 10W, Class 2	2-2
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 50W, Class 2	1-4

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00516	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	3-3

For other power supply options consult factory.

PHOTOMETRIC DATA

*Coming Soon**Job Name/Date:**Fixture Type Designation:*