

SPOT

PROJECTORS FOR OUTDOOR APPLICATIONS



Characterized by a perforated bracket, Spot projectors range from the ultra-compact version – an AISI 316L stainless steel body with a diameter of just 1.18" and 2W of power – to more powerful versions, with a body in Anticorodal aluminum and built-in power supply. The extreme resistance and reliability of this family makes it a safe and versatile choice for outdoor lighting. In addition to the white, anthracite and jasper green finishes, a customized RAL finish can be requested.

designplan® 

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

SPOT

2700K 3000K 4000K 5000K blue

max 500mA; 24... ; 120VAC
max 2W up to 50W
CRI 80
up to 4000 lm (3000K, 14°, 50W)
Optics
Fixed: 10°, 14°, 15°, 20°, 21°, 27°, 29°, 36°, 39°, 40°, 55°, 56°, 58°
Sharp: 19°, 54°
Elliptical: 14°x66°
IP66 IP68 IK07 IK08 IK09 IK10

Ø1.18"

Ø2.36"

Ø3.31"

Ø4.29"

Ø5.85"



SPOT 1.0
SPOT 1.6



SPOT 2.4





SPOT 3.4



SPOT 4.4



SPOT 5.4



Accessories:
Honeycomb louvre
Standard snoot
Asymmetrical snoot
Spike



Spot 2.4, 3000K, 8W, 58°, jasper green, with standard snoot and fastener strap.