


Visual is a unique, wall mounted luminaire with a steel structure and an elegant look. It is available with 3W of power, 2700K color temperature and a painted cream standard finish.

TECHNICAL DATA

Wattage	3W
Power Supply	Remote 350mA, not included. See page 2.
Light Source	Modulo LED
Construction	Body: Steel
CCT	2700K
CRI	>80
Delivered Lumens	180 lm
Efficacy	60 lm/w
Optics	Diffused
Finishes	Body: Cream Painted Details: Natural Brass
Fixture Dimensions	7.87 x 9.45 x 9.84 h
IP Rating	IP20



Fixture dimensions



7.87" x 9.45" x H 9.84"

Uses Remote Driver
Does not require a J-Box

ORDERING INFORMATION

Example: R70.103.8.ON.27.US. Power supplies ordered separately.

R70.103	8	ON	27	US
Model No.	Body Finish	Detail Finish	CCT	
R70.103	8 - Cream Painted	ON - Natural Brass	27 - 2700K	US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00496	Phase Dim (120V only)	120VAC to 350mA, 12W, Class 2, DAMP	1-3
PPLT00466-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 10W, Class 2, DAMP	1-5
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 50W, Class 2, DAMP	1-5

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00247	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 7W, Class 2	1-2
PPLT00516	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	2-3

*For other power supply options consult factory.***PHOTOMETRIC DATA***Coming Soon**Job Name/Date:**Fixture Type Designation:*