# **DIVAR RECESSED**



datasheet


Divar Recessed is a rectangular, recessed version of Divar suitable for outdoor installation in a variety of settings. It is made of extruded aluminum treated with electrophoresis and polyester powder coated, while the front ring is crafted from white-painted stainless steel. Available in 4 optics options (including diffused) and a standard white finish.

## **TECHNICAL DATA**

Wattage	15.4W (Optics), 7.2W (Diffuse)		
Power Supply	Integral 120VAC		
Construction	Body: Extruded Aluminum		
	Front Ring: Stainless Steel		
	Lens: Transparent or Sandblasted Glass		
CCT	2700K, 3000K		
CRI	>80		
BUG Rating	B2-U1-G0 (19°, 32° - 3000K)		
	B1-U0-G0 (60° - 3000K)		
	B0-U1-G0 (Diffuse - 3000K)		
<b>Delivered Lumens</b>	1177 lm (32°, 3000K)		
	527 lm (Diffuse, 3000K)		
Efficacy	76.4 lm/W (32°, 3000K)		
	73.2 lm/W (Diffuse, 3000K)		
Optics	19°, 32°, 65°, Diffuse		
LED Source	Power LED (15.4W)		
	Mid Power LED (7.2W)		
Finishes	White		
Fixture Dimensions	8.54" l x 2.83" w x 3.43" h		
IP Rating	IP65		
Impact Resistance	IK06		



**Fixture Dimensions** 



## **ORDERING INFORMATION**

Example: D901011152.US. Accessories ordered separately.

D9010			2	. US
Model #	ССТ	Optics	Finish	
D9010	<b>31</b> - 2700K <b>11</b> - 3000K	14 - 19° 15 - 32° 16 - 65° 17 - Diffuse (7.2W)	2 - White	US

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

# **DIVAR RECESSED**



datasheet

### **ACCESSORIES**






**D9079**Metal Box
For solid ceiling installation


#### **PHOTOMETRIC DATA**

Note: all photometry is 3000K


19°



32°




65°



PHOTOMETRIO FIEERAME : DIVAR REGESSED 13 \_3000R.IES

Diffuse



Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

2 of 2