

MOK BOLLARD 3300

180° EMISSION


MOK is a family of easy to install, durable LED fixtures that integrate into a variety of environments with wall, pole, or ceiling mounted versions, spotlights and bollards. MOK Bollard 3300 is a 130.0" height version with 180° light emission, suitable for outdoor installation and resistant to water thanks to its IP66, IP68 rating. It is available in 3 color temperatures and 3 standard finishes.

TECHNICAL DATA

Wattage	11W
Power Supply	Integral 120VAC
Construction	Body: Aluminum Lens: Extra Clear Tempered Glass
CCT	2700K, 3000K, 4000K
BUG Rating	B0-U1-G0
CRI	>80
Delivered Lumens	793 lm (3000K)
Efficacy	72.1 lm/W (3000K)
Optics	180°
Finishes	Anthracite, ALU Gray (RAL 9006), Dark Brown
Lumen Maintenance	85,000 hrs (Ta 35°C)
Fixture Dimensions	Ø6.61" x 5.87" w x 130.02" h
IP Rating	IP65, IP68 (Fast connection)
Impact Resistance	IK09



Fixture Dimensions



ORDERING INFORMATION

Example: F62068.1.2.64.US. Accessories sold separately.

F62068			64	US
Model No.	Finish	CCT	Optics	
F62068	1 - Anthracite 4 - ALU Gray (RAL 9006) 8 - Dark Brown	2 - 2700K 3 - 3000K 4 - 4000K	64 - Single Emission (180°)	US


Job Name/Date:

Fixture Type Designation:

MOK BOLLARD 3300

180° EMISSION

ACCESSORIES




PHOTOMETRIC DATA

Note: All Photometry is 3000K

Maximum Candela = 948.4

— C0 - C180
— C90 - C270



Job Name/Date:

Fixture Type Designation: