

# MOK BOLLARD 1000

## 360° EMISSION


MOK is a family of easy to install, durable LED fixtures that integrate into a variety of environments with wall, pole, or ceiling mounted versions, spotlights and bollards. MOK Bollard 1000 is a 42.0" height version with 360° light emission, suitable for outdoor installation and resistant to water thanks to its IP65, IP68 rating. It is available in 3 color temperatures and 3 standard finishes.



### TECHNICAL DATA

Wattage	22W
Power Supply	Integral 120VAC - On/Off
Construction	Housing: 6060 T5 Aluminum Lens: Extra Clear Tempered Glass
CCT	2700K, 3000K, 4000K
BUG Rating	B1-U1-G1
CRI	>80
Delivered Lumens	1585 lm (3000K)
Efficacy	72.1 lm/W (3000K)
Optics	360°
Finishes	Anthracite ALU Gray (RAL 9006) Dark Brown
Lumen Maintenance	85,000 hrs (Ta 35°C)
Fixture Dimensions	Ø6.61" x 5.87" w x 41.93" h
IP Rating	IP65, IP68 (Fast connection)
Impact Resistance	IK09

Fixture Dimensions



### ORDERING INFORMATION

Example: F62047.1.2.67.US. Accessories sold separately.

F62047			67	US
Model No.	Finish	CCT	Optics	
F62047	1 - Anthracite 4 - ALU Gray (RAL 9006) 8 - Dark Brown	2 - 2700K 3 - 3000K 4 - 4000K	67 - Double Emission (360°)	US


Job Name/Date:

Fixture Type Designation:

# MOK BOLLARD 1000

## 360° EMISSION


### ACCESSORIES



### PHOTOMETRIC DATA

*Note: All Photometry is 3000K*

Maximum Candela = 992.9



PHOTOMETRIC FILENAME : MOK 360° BOLLARD 1000 42IN 30K - 62047.X.3.67.IES

Job Name/Date:

Fixture Type Designation: