

MOK DOWNLIGHT


MOK is a family of easy to install, durable LED fixtures that integrate into a variety of environments with wall, pole, or ceiling mounted versions, spotlights and bollards. MOK Downlight is a Ø6.7" ceiling mounted version, suitable for outdoor installation and resistant to water thanks to its IP65, IP68 rating. It is available in 3 color temperatures, 3 optics options, and 2 standard finishes.



TECHNICAL DATA

Wattage	20W
Power Supply	Integral 120VAC - On/Off
Construction	Body: Aluminum Lens: Extra Clear Tempered Glass
CCT	2700K, 3000K, 4000K
BUG Rating	B2-U0-G0 (3000K)
CRI	>80
Delivered Lumens	2034 lm (3000K, 12°)
Efficacy	101.7 lm/W (3000K, 12°)
Optics	12°, 24°, 38°
Finishes	Pure White (RAL 9010) ALU Gray (RAL 9006)
Lumen Maintenance	55,000 hrs (Ta 35°C)
Fixture Dimensions	Ø6.69" x 5.91" w x 8.58" h
IP Rating	IP65, IP68 (Fast connection)
Impact Resistance	IK08

Fixture Dimensions



ORDERING INFORMATION

Example: F22022.2.2.11.US.

F22022				US
Model No.	Finish	CCT	Optics	
F22022	2 - Pure White (RAL 9010) 4 - ALU Gray (RAL 9006)	2 - 2700K 3 - 3000K 4 - 4000K	11 - 12° Spot 12 - 24° Medium 13 - 38° Wide	US


Job Name/Date:

Fixture Type Designation:

PHOTOMETRIC DATA


Note: All Photometry is 3000K

Maximum Candela = 14367.8




PHOTOMETRIC FILENAME : MOK DOWNLIGHT 30K 12° - 22022.X.3.11.IES

Maximum Candela = 8007.3



PHOTOMETRIC FILENAME : MOK DOWNLIGHT 30K 24° - 22022.X.3.12.IES

Maximum Candela = 4149.5



PHOTOMETRIC FILENAME : MOK DOWNLIGHT 30K 38° - 22022.X.3.13.IES

Job Name/Date:

Fixture Type Designation: