

MOK MINI FLOODLIGHT PRO RGBW


MOK is a family of easy to install, durable LED fixtures that integrate into a variety of environments with wall, pole, or ceiling mounted versions, spotlights and bollards. MOK Mini Floodlight Pro RGBW is the smaller floodlight (Ø4.3") offering RGBW light, rotatable 180° horizontally and 90° vertically, suitable for outdoor installation and resistant to water thanks to its IP65, IP68 rating. It is available in 5 optics options, and 3 standard finishes.



TECHNICAL DATA

Wattage	12W
Power Supply	Integral 120VAC - On-board DMX
Construction	Body: Aluminum Bracket: Stainless Steel Lens: Extra Clear Tempered Glass
CCT	RGBW
BUG Rating	—
CRI	>80
Delivered Lumens	253 lm: (R) 33 lm, (G) 84 lm, (B) 20 lm, (W) 116 lm (6500K)
Efficacy	21.1 lm/W: (R) 2.8 lm/W, (G) 7 lm/W, (B) 1.7 lm/W, (W) 9.7 lm/W (6500K)
Optics	10°, 25°, 45°, 10°x40°, 40°x10°
Finishes	Anthracite, ALU Gray (RAL 9006), Dark Brown
Lumen Maintenance	90,000 hrs (Ta 35°C)
Fixture Dimensions	Ø4.33" x 4.76"
IP Rating	IP65, IP68 (Fast connection)
Impact Resistance	IK08

Fixture Dimensions



ORDERING INFORMATION

Example: F42006.1.5.01.US. Accessories ordered separately.



F42006		5		US
Model No.	Finish	CCT	Optics	
F42006	1 - Anthracite 4 - ALU Gray (RAL 9006) 8 - Dark Brown	5 - RGB+W	01 - 10° Spot 36 - 25° Medium 32 - 45° Wide 70 - 10°x40° 38 - 40°x10°	US

Job Name/Date:


Fixture Type Designation:

ACCESSORIES

Installation / Anti-Glare




A9903
Steel Peg



L.MAX 6.56 ft




A0003
Anchoring Belt
L = 6.56 ft



A1801.
Aluminum visor for MOK Mini
1 - Anthracite
4 - ALU Gray (RAL 9006)
8 - Dark Brown
(To be ordered together with the product)

ACCESSORIES

Controllers (RGBW)



PPWD00570 - RGBW DMX512+Wifi Controller
Touch Sensitive
Can be controlled by WiFi
Controls 3 zones synchronously and separately

Job Name/Date:

Fixture Type Designation: