

CUPOLA 3


Cupola is an IP67-rated, in-grade uplight suitable for ground or wall installation, perfect for marking paths, transforming corridors and lighting stairs. It comes in 3 color temperatures and 4 different directional beam options. Cupola 3 is the triple direction beam version in a stainless steel or black oxide finish.

TECHNICAL DATA

Wattage / Input	4W
Power Supply	Remote 24VDC, not included. See page 2.
Construction	Body: Anodized Anticorodal Aluminum AISI 316L Stainless Steel Cable Length: 1.64'
CCT	2700K, 3000K, 4000K
BUG Rating	B0-U2-G1 (2700K)
Delivered Lumens	130.6 lm (2700K)
Efficacy	32.7 lm/W
Optics	Asymmetric
Finishes	Stainless Steel, Black Oxide
Fixture Dimensions	Ø3.14" x 1.68" h
Cut-Out Size	Ø2.1"
Color Consistency	<3-Step MacAdam
IP Rating	IP67
Impact Resistance	IK10
Driveover Capacity	Up to 6614 lbs



Fixture Dimensions



ORDERING INFORMATION

Example: CU3-L-30-AS-05. Accessories / Power Supplies ordered separately.

CU3-L	-		-	AS	-	
Model No.	CCT	Optic	Finish			
CU3-L - Triple Beam	27 - 2700K 30 - 3000K 40 - 4000K	AS - Asymmetric	05 - Stainless Steel BO - Black Oxide			

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00284	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, DAMP	1-20

SUGGESTED POWER SUPPLIES

Remote 24VDC Driver in NEMA 4X Enclosure - ELV / TRIAC / 0-10V




PPLT00715

Part Number	Description	Input/Output	# of Fixtures
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-19

For other power supply options consult factory.

ACCESSORIES - Installation



PPMP03486

Core Drilled Application Sleeve


Sizes Ø2.5" x 5.9" h

For in-grade use

PHOTOMETRIC DATA

Note: All photometric data is 3000K

Maximum Candela = 87.2



PHOTOMETRIC FILENAME : CUPOLA 3.IES

Job Name/Date:

Fixture Type Designation: