BOA WALL OUT

designplan

datasheet

Boa Wall Out is a rectangular, surface mounted wall light that brings style and technical expertise together with a clearly defined light beam up and/or down. It is available in 2 color temperatures and 3 standard finishes.

Fixture Dimensions



TECHNICAL DATA

Wattage	7W
Power Supply	Remote 700mA, not included. See page 2.
Construction	—
CCT	2700K, 3000K (4000K on request)
CRI	>90
Delivered Lumens	700 lm (3000K)
Efficacy	70 lm/W
Optics	—
Finishes	4 Standard Combinations, see below
Fixture Dimensions	5.91” x 1.97” x 7.87” h
Fixture Weight	2.43 lbs
LED Source	CLARA AC
Lumen Maintenance	50,000 hrs (Ta 25°C)
Color Consistency	3-Step MacAdam
IP Rating	IP65

ORDERING INFORMATION

Example: T433992. Power Supplies ordered separately.

Model No.	Description
T406410	2700K, Textured White + Silver Anodized
T406470	2700K, Textured Black + Silver Anodized
T406430	2700K, Textured Gray + Silver Anodized
T406426	2700K, Textured Black + Gold Anodized
T406400	3000K, Textured White + Silver Anodized
T406460	3000K, Textured Black + Silver Anodized
T406420	3000K, Textured Gray + Silver Anodized
T406416	3000K, Textured Black + Gold Anodized

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825
© Copyright 2026 Designplan Lighting, Inc.
Published: April 14, 2026
P: 908-996-7710
F: 908-996-7042

SUGGESTED POWER SUPPLIES

700mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00498	Phase Dim (120V only)	120VAC to 700mA, 12W, Class 2, DAMP	1-2
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 20W, Class 2, DAMP	1-2
PPLT00261	Leading / Trailing Edge Dimming to 10% (120V only)	120-277VAC to 700mA, 32W, Class 2	3-4
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 700mA, 50W, Class 2, DAMP	1-5

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00515	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 700mA, 14W, Class 2	2-2
PPLT00635	PEQ0E	PEQ0	100%-1%	Hi-Lume™ Premier 0.1% EcoSystem™ F2B LED Driver	120/277VAC to 700mA, 20W, Class 2	2-2

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825

© Copyright 2026 Designplan Lighting, Inc.

Published: April 14, 2026

P: 908-996-7710
F: 908-996-7042