

NEVA PRO 7 SURFACE

NEVA PRO 7.0, 7.1, 7.2 and NEVA MINI PRO 7

The Neva Pro 7 series are frameless linear profiles designed to enhance wall and facades with new generation optics with a variety of well-defined beams. Available with RGBW light and 4 different lengths with in-grade housing for recessed applications or adjustable brackets for surface mount.

TECHNICAL DATA

Wattage / Input	See Chart on page 2. (24VDC)
Power Supply	Remote, not included. See page 3.
Construction	Body: Black Painted Anodized Aluminum Lens: Transparent or Acid-Etched Tempered Glass Cable Length: 4.92' standard
CCT	RGBW
CRI	>80
Delivered Lumens	See Chart on page 2 for Lumens / Efficacy
LED Spacing	2.36" between
Optics	Optics: 15°, 30°, 52°, 20°x55°, Diffuse Linear: 40°x88°, Wall Washer
Finishes	Black
Fixture Dimensions / Wt.	See Chart on page 2
LED Source	See Chart on page 2
Lumen Maintenance	L90, B10 >50,000 hrs (Ta 25°C)
Color Consistency	—
Operating Temp.	-4°F to +122°F
IP Rating	IP66, IP67
Impact Rating	IK06



ORDERING INFORMATION

Example: NP7100000170MN or NP7100000170MN-2. Accessories / Power Supplies ordered separately.

		7		N
Model No. NP0700 - Neva Pro Mini 7 (16W) NP7000 - Neva Pro 7.0 (32W) NP7100 - Neva Pro 7.1 (49W) NP7200 - Neva Pro 7.2 (81W)	Optical Accessories 0000 - none 0001 - Honeycomb 0004 - Micro Louver NOTE: Honeycomb Louver NOT available with Diffuse or Wall Washer optics. Micro Louver ONLY available with 40°x88° and Wall Washer optics.	CCT 7 - RGBW	Optics 0S - 15° 0M - 30° 0L - 52° 0W - 20°x55° LW - 40°x88° 0D - Diffuse (only on None or Honeycomb) LA - Wall Washer (only on Micro Louver)	Finish N - Black

Job Name/Date:

Fixture Type Designation:

NEVA PRO 7 SURFACE


NEVA PRO 7.0, 7.1, 7.2 and NEVA MINI PRO 7

TECHNICAL DATA


	NEVA MINI PRO 7	NEVA PRO 7.0	NEVA PRO 7.1	NEVA PRO 7.2
Wattage	16W	32W	49W	81W
Delivered Lumens (30K, 15°)	662 lm: (R) 145 lm, (G) 269 lm, (B) 60 lm, (W) 258 lm	1324 lm: (R) 290 lm, (G) 538 lm, (B) 120 lm, (W) 516 lm	1986 lm: (R) 435 lm, (G) 807 lm, (B) 180 lm, (W) 774 lm	3310 lm: (R) 725 lm, (G) 1345 lm, (B) 300 lm, (W) 1290 lm
Fixture Dim. (l,w,h)	12.44" x 1.46" x 2.28"	24.25" x 1.46" x 2.28"	36.06" x 1.46" x 2.28"	59.72" x 1.46" x 2.28"
Fixture Weight	1.32 lbs	2.54 lbs	3.64 lbs	6.06 lbs
LED Source	84 mid power full color + white LEDs, 5 high intensity power multicolor LEDs	168 mid power full color + white LEDs, 10 high intensity power multicolor LEDs	252 mid power full color + white LEDs, 15 high intensity power multicolor LEDs	420 mid power full color + white LEDs, 25 high intensity power multicolor LEDs




NEVA MINI PRO 7



NEVA PRO 7.0



NEVA PRO 7.1



NEVA PRO 7.2

Job Name/Date:

Fixture Type Designation:

NEVA PRO 7 SURFACE

NEVA PRO 7.0, 7.1, 7.2 and NEVA MINI PRO 7

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures / Power Supply			
			Neva Pro Mini 7	Neva Pro 7.0	Neva Pro 7.1	Neva Pro 7.2
			16W	32W	49W	81W
PPLT00288-P	DMX / RDM (Field Addressable) / DALI	120-277VAC to 24VDC, 100W, Dry	1-5	1-2	1-1	Consult Factory

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:

NEVA PRO 7 SURFACE

NEVA PRO 7.0, 7.1, 7.2 and NEVA MINI PRO 7

ACCESSORIES - Installation



WMA09N
Pair of Brackets
2.95" h




WMA10N
Pair of Brackets
5.51" h




WN6001
Fixture Anti Fall Kit
*Optional for Ceiling Installations
(and if desired Wall)*

Anti-Glare



Honeycomb Louver
Optical Accessory
Built in - Order with fixture code



Micro Louver
Optical Accessory
Built in - Order with fixture code



Anti-Glare Shield
Stainless steel painted black
WB6500 - Neva Pro Mini 7 (12.91")
WB6520 - Neva Pro 7.0 (26.50")
WB6521 - Neva Pro 7.1 (40.67")
WB6522 - Neva Pro 7.2 (69.06")

Job Name/Date:

Fixture Type Designation:


NEVA PRO 7 SURFACE

NEVA PRO 7.0, 7.1, 7.2 and NEVA MINI PRO 7

PHOTOMETRIC DATA


Note: All photometry is 3000K

Maximum Candela = 4455.5




PHOTOMETRIC FILENAME : NEVA_MINI_PRO_7_S_15_RGBW_16W_24VDC.IES

Maximum Candela = 1038.6




PHOTOMETRIC FILENAME : NEVA_MINI_PRO_7_W_20X55_RGBW_16W_24VDC.IES

Maximum Candela = 1650.1




PHOTOMETRIC FILENAME : NEVA_MINI_PRO_7_M_30_RGBW_16W_24VDC.IES

Maximum Candela = 580.1




PHOTOMETRIC FILENAME : NEVA_MINI_PRO_7_40X88_RGBW_16W_24VDC.IES

Maximum Candela = 577.6




PHOTOMETRIC FILENAME : NEVA_MINI_PRO_7_L_52_RGBW_16W_24VDC.IES

Maximum Candela = 122.7



PHOTOMETRIC FILENAME : NEVA_MINI_PRO_7_DIFFUSE_RGBW_16W_24VDC.IES

Maximum Candela = 427.3



PHOTOMETRIC FILENAME : NEVA_MINI_PRO_7_WALLWASHER_RGBW_16W_24VDC.IES

Job Name/Date:

Fixture Type Designation:


NEVA PRO 7 SURFACE

NEVA PRO 7.0, 7.1, 7.2 and NEVA MINI PRO 7

PHOTOMETRIC DATA


Note: All photometry is 3000K

Maximum Candela = 8911




PHOTOMETRIC FILENAME : NEVA_PRO_7.0_S_15_RGBW_32W_24VDC.IES

Maximum Candela = 2077.2




PHOTOMETRIC FILENAME : NEVA_PRO_7.0_W_20X55_RGBW_32W_24VDC.IES

Maximum Candela = 3300.2




PHOTOMETRIC FILENAME : NEVA_PRO_7.0_M_30_RGBW_32W_24VDC.IES

Maximum Candela = 1160.1




PHOTOMETRIC FILENAME : NEVA_PRO_7.0_40X88_RGBW_32W_24VDC.IES

Maximum Candela = 1155.2




PHOTOMETRIC FILENAME : NEVA_PRO_7.0_L_52_RGBW_32W_24VDC.IES

Maximum Candela = 245.4



PHOTOMETRIC FILENAME : NEVA_PRO_7.0_DIFFUSE_RGBW_32W_24VDC.IES

Maximum Candela = 854.7



PHOTOMETRIC FILENAME : NEVA_PRO_7.0_WALLWASHER_RGBW_32W_24VDC.IES

Job Name/Date:








Fixture Type Designation:

NEVA PRO 7 SURFACE

NEVA PRO 7.0, 7.1, 7.2 and NEVA MINI PRO 7

PHOTOMETRIC DATA

Note: All photometry is 3000K



Job Name/Date:

Fixture Type Designation:


NEVA PRO 7 SURFACE

NEVA PRO 7.0, 7.1, 7.2 and NEVA MINI PRO 7

PHOTOMETRIC DATA


Note: All photometry is 3000K

Maximum Candela = 22277.5




PHOTOMETRIC FILENAME : NEVA_PRO_7.2_S_15_RGBW_81W_24VDC.IES

Maximum Candela = 5192.9




PHOTOMETRIC FILENAME : NEVA_PRO_7.2_W_20X55_RGBW_81W_24VDC.IES

Maximum Candela = 8250.5




PHOTOMETRIC FILENAME : NEVA_PRO_7.2_M_30_RGBW_81W_24VDC.IES

Maximum Candela = 2900.3




PHOTOMETRIC FILENAME : NEVA_PRO_7.2_40X88_RGBW_81W_24VDC.IES

Maximum Candela = 2888.0




PHOTOMETRIC FILENAME : NEVA_PRO_7.2_L_52_RGBW_81W_24VDC.IES

Maximum Candela = 613.5



PHOTOMETRIC FILENAME : NEVA_PRO_7.2_DIFFUSE_RGBW_81W_24VDC.IES

Maximum Candela = 2136.7



PHOTOMETRIC FILENAME : NEVA_PRO_7.2_WALLWASHER_RGBW_81W_24VDC.IES

Job Name/Date:

Fixture Type Designation: