ITACA

datasheet

Itaca is a wall mounted luminaire with a sophisticated geometric shape that is suitable for installation in outdoor living areas, entrances, stairways, walkways or anywhere a directed light is needed. It is available in 4 sizes, 2 color temperatures and 6 standard finishes. Fixtures are Class 2 low voltage and do not require a J-box.



ADA Compliant

TECHNICAL DATA

Wattage	1.9W (Itaca 45) 4.1W (Itaca 90) 6W (Itaca 135) 8W (Itaca 180)
Power Supply	Remote 24VDC, not included. See page 2
Construction	Body: Anodized Alloy Aluminum Lens: Textured, Sandblasted Glass
CCT	2700K, 3000K
CRI	>80
BUG Rating	Coming Soon
Delivered Lumens	Coming Soon
Efficacy	Coming Soon
Optics	Diffuse
LED Source	Mid Power LED
Finishes	6 Standard, See Below
Fixture Dimensions	1.7” x 3.5” x 1.8”, 3.5”, 5.3” or 7.1” wide
IP Rating	IP66
Impact Resistance	IK07

Fixture Dimensions









ORDERING INFORMATION

Example: D903012024.US. Accessories / Power Supplies ordered separately.

D9030				.	US
Model #	**CCT**	**Optics / Wattage**	**Finish**		
D9030	**32** - 2700K **12** - 3000K	**00** - Itaca 45 (1.9W) **01** - Itaca 90 (4.1W) **02** - Itaca 135 (6W) **03** - Itaca 180 (8W)	**2** - White **3** - Sand **4** - Graphite **5** - Aluminum **8** - Corten **16** - Green		**US**

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825

© Copyright 2026 Designplan Lighting, Inc.

Published: November 16, 2026

P: 908-996-7710
F: 908-996-7042

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures			
			Itaca 45	Itaca 90	Itaca 135	Itaca 180
PPLT00284	Non-Dim	120-277VAC to 24VDC, 100W, Class 2	1-42	1-19	1-13	1-10
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	5-42	2-19	1-13	1-10

Suggested Lutron Compatible - Itaca 45

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3DAE / L3D0	L3DA/L3D0	100%-1%	Hi-Lume™ 0.1% EcoSystem™ or 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-40

Suggested Lutron Compatible - Itaca 90

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3DAE / L3D0	L3DA/L3D0	100%-1%	Hi-Lume™ 0.1% EcoSystem™ or 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-18

Suggested Lutron Compatible - Itaca 135

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3DAE / L3D0	L3DA/L3D0	100%-1%	Hi-Lume™ 0.1% EcoSystem™ or 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-12

Suggested Lutron Compatible - Itaca 180

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3DAE / L3D0	L3DA/L3D0	100%-1%	Hi-Lume™ 0.1% EcoSystem™ or 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-9

DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures			
			Itaca 45	Itaca 90	Itaca 135	Itaca 180
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-40	1-18	1-12	1-9

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:

© Copyright 2026 Designplan Lighting, Inc.
Published: November 16, 2026

ACCESSORIES

Installation





D9018
Recessed Box
2.8" x 2.8" x 2.1"
For Itaca 90 and 135 installation





D9019
Recessed Box
2.9" x 4.2" x 2.1"
For Itaca 135 and 180 installation

PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825

© Copyright 2026 Designplan Lighting, Inc.

Published: November 16, 2026

P: 908-996-7710
F: 908-996-7042