MICRO 3

datasheet

Micro 3 is a miniature, surface mounted luminaire that can be installed on ceilings or walls. It is 3.5 inches in diameter, and available in 3 color temperatures, 4 optics options that can be changed in the field and 4 standard finishes.






TECHNICAL DATA

Wattage	12W
Power Supply	Remote 350mA, not included. See page 2
Construction	Body: Aluminum Lens: Glass
CCT	2700K, 3000K, 4000K
CRI	>90
Delivered Lumens	Coming Soon
Efficacy	Coming Soon
Optics	15°, 24°, 36°, 50°
LED Source	BRIDGELUX GEN8 COB LED
Finishes	White, Black, Black Anodized, Silver Anodized, Custom RAL on request
Fixture Dimensions	Ø3.46” x 3.07” h
IP Rating	IP20

Fixture Dimensions



ORDERING INFORMATION

Example: MI3-L-30-97-24-H-R-0. Power Supplies ordered separately.

MI3-L	-		-		-		-	R	-	0

Model #	CCT	Finish	Optics	Lens	Dimming / Driver	Options
MI3-L	**27** - 2700K **30** - 3000K **40** - 4000K	**11** - White **02** - Black **97** - Black Anodized **TG** - Titanium Grey **C** - Custom RAL	**15** - 15° **24** - 24° **36** - 36° **50** - 50°	**H** - Clear w/ Honeycomb **C** - Clear	**R** - Remote Driver (Static White)	**0** - None

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825
© Copyright 2026 Designplan Lighting, Inc.
Published: November 25, 2026
P: 908-996-7710
F: 908-996-7042

SUGGESTED POWER SUPPLIES

Static White - 350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 50W, Class 2, DAMP	1-1
PPLT00467-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 50W, Class 2, DAMP	1-1

For other power supply options consult factory.

PHOTOMETRIC DATA

Note: Photometry is 3000K

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825

© Copyright 2026 Designplan Lighting, Inc.

Published: November 25, 2026

P: 908-996-7710
F: 908-996-7042